



CyberPower OLS3000EA-DE uninterruptible power supply (UPS) Double- conversion (Online) 3 kVA 2700 W 7 AC outlet(s)

Modelis: OLS3000EA-DE

Gamintojas: CYBERPOWER

EAN: 4711027790251

Prekės kodas: 584068

604.99€

Certification: RoHS, CE | Form factor: Tower | Package width: 295 mm | Operating temperature (T-T): 0 - 40 °C | Package height: 458 mm | Output operation voltage (min): 208 V | Surge energy rating: 370 J | Audible alarm modes: Battery replacement, Fault, Low battery alarm, Overload alarm | Harmonized System (HS) code: 8504408590 | Width: 196 mm | UPS topology: Double-conversion (Online) | Number of batteries supported: 3 | Maximum current: 13.04 A | Depth: 416 mm | Input frequency: 50/60 Hz | Typical backup time at half load: 13.1 min | Output voltage Total Harmonic

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Distortion (THD): 5% | Storage relative humidity (H-H): 10 - 90% | Output power capacity: 3 kVA | Output power: 2700 W | LED indicators: Power | EMI/RFI noise filtering: Yes | Storage temperature (T-T): -20 - 50 °C | Input operation voltage (min): 190 V | Response time: 0 ms | Cable length: 1.5 m | Crest factor: 3:1 | Power factor: 0.9 | Waveform: Pure sine | Output frequency: 50/60 Hz | AC outlets quantity: 7 AC outlet(s) | Input power factor: 0.98 | USB port: Yes | Audible alarm(s): Yes | Built-in fan: Yes | AC outlet types: C13 coupler | Battery technology: Sealed Lead Acid (VRLA) | Display type: LCD | LED indicators: Status | LED indicators: Operation | Operating altitude: 0 - 1500 m | Operating relative humidity (H-H): 20 - 90% | Typical backup time at full load: 4.2 min | Weight: 21.3 kg | Surge protection: Yes | Cables included: Power load cable, USB cable | Housing material: Metal | Power protection features: Overload | Efficiency (ECO mode): 95% | Product colour: Black | Non-operating altitude: 0 - 1500 m | Output operation voltage (max): 240 V | LED indicators: Fault | Input operation voltage (max): 230 V | Charging current: 1.5 A | Battery recharge time: 4 h | Height: 337 mm | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock.