



TP-Link Tapo Solar-Powered Pan/Tilt Security Camera Kit

Modelis: Tapo C610 KIT

Gamintojas: TP-LINK

EAN: 8885020629651

Prekės kodas: 584316

91.98€

Certification: CB, CE, FCC, DOE, CEC, RCM, KC, JFR,VCCI,NCC, BSMI, NTRA, IP65 | Connectivity technology: Wireless | Product colour: White | Tilt angle range: 90 - 130° | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Width: 141 mm | Battery technology: Lithium-Ion (Li-Ion) | Supported graphics resolutions: 2304 x 1296 | Built-in light: Yes | Audio output channels: 2.0 channels | Operating relative humidity (H-H): 10 - 90% | Package weight: 1.34 kg | AC input frequency: 50-60 Hz | Compatible memory cards: MicroSD (TransFlash) | Package height: 240 mm | Package width: 145 mm | Depth: 84 mm | Maximum resolution: 2304 x 1296 pixels | Reset button: Yes | Number of batteries supported: 1 | Security algorithms: SSL/TLS | Weight: 590 g | Type: IP security camera | AC input voltage: 100-240 V | Package depth: 193 mm | Form factor: Turret | Wi-Fi: Yes | Security algorithms: WPA | Ethernet LAN: Yes | Networking standards: IEEE 802.11b | Storage relative humidity (H-H): 0 - 90% | Audio system: 2-way | International Protection (IP) code: IP65 | Microphone in: Yes | Operating temperature (T-T): -20 - 45 °C | Storage temperature (T-T): -20 - 60 °C | Built-in microphone: Yes | Power source type: Battery, Solar | Mobile operating systems supported: iOS 12 | LED type: IR | Number of lenses: 1 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Video motion detection: Yes | Number of cameras: 1 | Number of sensors: 1 | Total megapixels: 3 MP
| Optical sensor size: 50.8 / 8 mm (2 / 8") | Sensor type: CMOS | Night vision distance: 10 m | Live
view: Yes | Customs product code (TARIC): 8517790000 | Motion sensor: Yes | Camera tilt control:
Yes | Built-in HDD: No | Camera pan control: Yes | Mounting type: Ceiling/Wall/Pole | Infra-red
wavelength: 850 nm | Alert notification type: Snapshot alert message | Mobile operating systems
supported: Android 7.0 | PTZ control: Yes | Built-in speaker(s): Yes | Wide Dynamic Range (WDR): Yes
| Maximum memory card size: 512 GB | Lens viewing angle, diagonal: 100.6° | Lens viewing angle,
horizontal: 84.4° | Height: 128 mm | Image quality adjustment: DNR | Placement supported: Outdoor
| Noise reduction: Yes | Weatherproof: Yes | Cloud-managed: Yes | Maximum aperture number: 1.4 |
Audio input channels: 2.0 channels | Zoom capability: Yes | Night vision: Yes | Number of
microphones: 1 | Frame rate: 15 fps | Fixed focal length: 4 mm | Built-in siren: Yes | Siren noise level:
97.2 dB | Lens viewing angle, vertical: 44.3°