



## GODOX V1 TTL Flash for Sony



Modelis: V1S

Gamintojas: GODOX

EAN: 6952344217467

Prekės kodas: 584495

# 245.99€

### GODOX V1S Flash for Sony

The GODOX V1S Flash for Sony is a round-head news flash designed for Sony cameras equipped with a Multi Interface Shoe (MIS). It offers 76 Ws of power, TTL auto mode, high-speed sync (HSS) with fast shutter speeds, and the built-in Godox X 2.4 GHz wireless system. Powered by a high-capacity VB26 lithium-ion battery, with a fast recharge time to full power of approximately 1.5 seconds and extensive control options, the V1S is ideal for news photography, portrait sessions, and studio work.

### Soft and Even Light

The round flash head is designed to ensure even light distribution from the center all the way to the edges of the frame. This results in more natural lighting that works well when photographing people, events, and shots requiring aesthetically pleasing light. An additional feature is the built-in LED modeling light with 10-step power adjustment, which makes it easier to assess the lighting effect before taking the photo.

## Fast and Convenient Operation

The light uses a removable VB26 lithium-ion battery, which ensures a stable power supply during shooting. It takes a maximum of 1.5 seconds to fully charge, so the device is ready to take more photos even during fast-paced sessions. The head's wide adjustment range—from -7° to 120° vertically and from 0° to 330° horizontally—makes it easy to bounce light off walls and ceilings.

## Godox X Wireless System

The built-in 2.4 GHz Godox X system allows for compatibility with other strobes and triggers that support this standard. The V1S model supports both Master and Slave modes and allows you to control lighting across up to 5 groups and 32 channels, making it easy to set up complex lighting rigs. The magnetic accessory mount allows you to quickly attach compatible light modifiers without the need for additional adapters.

## Advanced features for demanding photographers

The GODOX V1S offers full TTL automation, manual mode, HSS synchronization, second-curtain sync, flash exposure compensation (FEC), and Multi-stroboscopic mode. The manually or automatically adjustable zoom range of 28–105 mm allows you to adapt the beam angle to the scene being photographed. Software updates can be performed via the USB port, ensuring the flash remains compatible with the manufacturer's latest features.

- GODOX V1S Flash
- VB26 Lithium-Ion Battery
- Charger
- USB Cable
- Hot Shoe
- Carrying Case
- User Manual

|                                      |                                            |
|--------------------------------------|--------------------------------------------|
| <b>Manufacturer</b>                  | GODOX                                      |
| <b>Model</b>                         | V1S                                        |
| <b>Compatibility</b>                 | Sony cameras with MIS hot shoe             |
| <b>Flash Power</b>                   | 76 Ws                                      |
| <b>Color Temperature</b>             | 5600 ±200 K                                |
| <b>Flash Duration</b>                | 1/350 – 1/20,000 s                         |
| <b>Recycle time</b>                  | max. 1.5 s                                 |
| <b>Zoom</b>                          | 28-105 mm                                  |
| <b>Vertical head adjustment</b>      | -7° to +120°                               |
| <b>Horizontal head adjustment</b>    | 0°-330°                                    |
| <b>Power supply</b>                  | VB26 lithium-ion battery                   |
| <b>Triggering</b>                    | hot shoe, TEST button, Godox X system      |
| <b>Power control</b>                 | TTL, manual, Godox X system                |
| <b>Operating modes</b>               | TTL / M / Multi / S1 / S2 / Master / Slave |
| <b>HSS synchronization</b>           | yes                                        |
| <b>Number of groups and channels</b> | 5 groups / 32 channels                     |
| <b>Display</b>                       | LCD                                        |
| <b>Software update</b>               | USB                                        |
| <b>Dimensions</b>                    | 7.6 × 9.3 × 19.7 cm                        |
| <b>Weight</b>                        | 0.54 kg (with battery)                     |

GPSR Link: <https://psr->

[assets.innpro.pl/photo\\_and\\_accessories/sg\\_photo\\_and\\_accessories\\_photo\\_accessories.pdf](https://assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf), Gross weight: 980, Net weight: 970, Box length: 22,00, Box width: 19,50, Box height: 11,50

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903