



GODOX TT600 Flash



Modelis: TT600

Gamintojas: GODOX

EAN: 6952344209806

Prekės kodas: 584505

104.99€

GODOX TT600 Flash

The GODOX TT600 Flash is a versatile manual news flash designed for Canon, Nikon, Fuji, Olympus, and Pentax cameras. It offers a guide number of 60 (ISO 100, 200 mm), a built-in Godox X 2.4 GHz radio system receiver, HSS synchronization support with a compatible transmitter, manual power adjustment from 1/1 to 1/128, and a swivel head with a 360° rotation range and a tilt range from -7° to 90°. Powered by four AA batteries, it delivers approximately 230 full-power flashes, with a recharge time ranging from 0.1 to 2.6 seconds. This model is designed for photographers who prefer full control over flash settings and want to create a flexible lighting system for both studio and outdoor photography.

Manual Light Control

The GODOX TT600 is designed for photographers who prefer to set their own lighting parameters. Flash power adjustment ranging from 1/1 to 1/128 in 1/3 EV increments allows you to precisely adjust the amount of light for any scene. The flash generates light with a color temperature of 5600K

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(with a tolerance of +/- 200K), which corresponds to natural daylight and facilitates accurate white balance adjustment. The lack of an automatic TTL mode gives you full control over the final result and allows you to achieve consistent results across consecutive shots, whether in the studio or on location.

Built-in Godox X Radio System

The flash is equipped with a 2.4 GHz Godox X wireless system receiver, allowing it to be conveniently controlled using compatible transmitters. The system supports 32 channels and 5 groups, making it easier to manage multiple flash units and reducing the risk of interference during operation. When used with a compatible transmitter, the TT600 also supports HSS synchronization, enabling photography with fast shutter speeds. Additionally, the housing features a slot for a 433 MHz receiver, allowing the flash to work with older trigger systems as well.

Movable Head and Wide Zoom Range

The flash head rotates 360° and tilts from -7° to 90°, allowing you to conveniently bounce light off walls and ceilings and create more natural lighting for the scene you're photographing. The built-in zoom covers a range from 20 to 200 mm, allowing you to adjust the light beam to match the focal length of your lens. An additional 14 mm wide-angle panel allows for comfortable use with wide-angle lenses. The flash also features an optical Master/Slave mode, enabling it to work with other flashes when setting up complex lighting rigs.

Powerful Performance and Quick Readiness

The TT600 is powered by four AA batteries, so it does not require dedicated rechargeable batteries. One set of batteries allows for approximately 230 full flashes, which is ideal for longer photo sessions. A recharge time ranging from 0.1 to a maximum of 2.6 seconds allows you to efficiently take consecutive photos without long waits. An additional advantage is the socket for connecting an external battery pack, which enhances comfort during intensive shooting.

Included in the set

- GODOX TT600 flash

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Stand
- Protective case
- Manufacturer's packaging

Manufacturer	GODOX
Model	TT600
Flash type	Manual flash
Compatibility	Canon, Nikon, Fuji, Olympus, Pentax
Guide number	60 (ISO 100, 200 mm)
Color temperature	5600K ±200K
Power adjustment	from 1/1 to 1/128 (in 1/3 EV steps)
Zoom	20-200 mm
Wide-angle panel	14 mm
Vertical head tilt	from -7° to +90°
Horizontal head rotation	360°
HSS synchronization	Yes (with a compatible transmitter)
Radio system	Godox X 2.4 GHz
Groups / channels	5 / 32
Trigger modes	Hot shoe, test button, System X, M, S1, S2, Slave
Stroboscopic mode (Multi)	Yes
Sync port	3.5 mm
Battery pack slot	Yes
Power supply	4 × AA batteries (not included)
Number of flashes	approximately 230 full flashes
Recycle time	0.1-2.6 s

GPSR Link: [https://psr-](https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf)

[assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf](https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf), Gross weight: 520, Net weight: 455, Box length: 19,50, Box width: 7,50, Box height: 10,50

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903