



GODOX TT685IIF TTL Flash for Fujifilm



Modelis: TT685IIF

Gamintojas: GODOX

EAN: 6952344223819

Prekės kodas: 584514

160.99€

GODOX TT685IIF Flash for Fujifilm

The Godox TT685IIF Fuji flash is designed for Fujifilm system cameras, offering a wide range of capabilities for both studio and outdoor photography. With a guide number of 60 (ISO 100, 200 mm), 76 Ws of power, and support for TTL auto mode and HSS synchronization up to 1/8000 s, it allows you to capture properly exposed photos even in challenging conditions. The head, with a zoom range of 20–200 mm, allows for precise adjustment of the light beam to the scene being photographed, making the flash ideal for both wide-angle shots and photos taken from greater distances.

Automatic Mode and Full Control Over the Flash

Compatibility with the Fuji system allows you to take advantage of the flash's many automatic functions, making it easier to work during dynamic photo shoots. Users have access to TTL, Multi, M, S1, and S2 modes, as well as Master and Slave operation. An additional convenience is the TCM (TTL Converted to Manual) function, which allows for instant conversion of settings from TTL mode to

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

manual mode, helping you quickly maintain proper exposure and simplifying the configuration of external flashes.

The Advanced Godox X Radio System

The built-in 2.4 GHz Godox X radio system allows the flash to function as both a transmitter and a receiver. With a range of up to 100 meters, support for 32 channels, and 5 groups, it offers great flexibility when setting up multi-unit lighting rigs. The flash is compatible with devices from the Godox V1, AD200Pro, and AD300Pro series, and can also be controlled using the X1, X2, XPro, and V1 transmitters, making it easy to create professional lighting setups.

Flexible Operation in Any Conditions

The flash head offers automatic or manual zoom ranging from 20 to 200 mm, allowing you to conveniently adjust the beam angle to suit the current situation. Additionally, it can be tilted from -7° to 120° and rotated through 330°, which makes it much easier to bounce light off walls or the ceiling and allows you to achieve more natural lighting effects when shooting in various locations.

Efficient Power Supply and Convenient Operation

The Godox TT685II Fuji is powered by four AA batteries, which allow for a minimum of 360 full flashes, and the maximum recharge time is 2.6 seconds. An external battery pack slot allows you to connect an additional power source, increasing performance during long photo sessions. The easy-to-read LCD display makes it simple to control all settings, the 2.5 mm sync port enables wired triggering, and the USB-C connector allows for future software updates.

Included

- Godox TT685II Fuji flash x1
- Stand x1
- Carrying case x1
- Packaging x1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Manufacturer	Godox
Model	TT685II Fuji
Compatibility	Fuji
Guide number	60 (ISO 100 @ 200 mm)
Power	76 Ws
Color temperature	5600 K ±200 K
Zoom	20-200 mm
Vertical head tilt	-7° to +120°
Horizontal head tilt	0° to 330°
Triggering	Hot shoe, test button, X-system
Power Supply	4 × AA (R6, not included)
Maximum Recycle Time	2.6 s
Flash Output Capacity	Minimum 360 full flashes
HSS Synchronization	Yes
Groups/Channels	5/32
Power Control	Continuously adjustable from the flash unit, X system
Trigger Modes	TTL / Multi / M / S1 / S2 / Master / Slave
Display	LCD
Battery pack slot	Yes

GPSR Link: <https://psr->

[assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf](https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf), Gross weight: 540, Net weight: 474, Box length: 19,00, Box width: 7,50, Box height: 10,50

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903