



GODOX V1 TTL Flash for Canon



Modelis: V1C

Gamintojas: GODOX

EAN: 6952344217184

Prekės kodas: 584517

248.99€

GODOX V1C Flash for Canon

The Godox V1 is an advanced flash for Canon cameras that combines 76Ws of power with a round head that provides soft and even lighting. Full TTL automation, HSS synchronization, a recharge time of just 1.5 seconds, and a high-capacity lithium-ion battery capable of delivering at least 460 full flashes make this model ideal for dynamic photo shoots. The wide range of head adjustments and extensive control functions ensure flexibility whether working in the studio or on location.

Soft and even light thanks to the round head

The flash is equipped with a round flash head that ensures even light distribution from the center all the way to the edges of the frame. As a result, the lighting resembles the effect seen with studio lights and allows you to achieve aesthetically pleasing results. An additional feature is the built-in LED modeling light with power adjustment ranging from 1 to 10, which makes it easier to assess lighting effects before taking a photo.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

High-Capacity Battery and Fast Recycle Time

The Godox V1 uses a removable VB26 lithium-ion battery with a capacity of 2600 mAh, which provides at least 460 full flashes on a single charge. The flash's short recharge time of up to 1.5 seconds allows you to quickly take consecutive photos without long waits. This feature is ideal for photographing dynamic events where every moment counts.

Wireless Control and Extensive Operating Capabilities

The built-in Godox X 2.4G system receiver enables compatibility with other devices operating within this system. The flash can operate in both Master and Slave modes and supports up to five groups and 32 channels, making it easy to set up complex lighting rigs. Available trigger options include TTL, Multi, M, S1, and S2 modes, as well as operation as a Master or Slave unit.

Flexible lighting setup and convenient operation

The wide range of head adjustment enhances the possibilities for creative use of reflected light. The head rotates horizontally from 0° to 330° and tilts vertically from -7° to +120°, making it easy to adjust the flash direction to suit the scene being photographed. The magnetic accessory mounting system allows for quick attachment of compatible accessories, such as the AK-R1 kit, and the sturdy hot shoe mount ensures the flash is securely attached to the camera. Software updates can be performed via the USB port.

Advanced Features for Greater Control

The V1 model offers full TTL automation as well as the option to operate in manual mode. It supports synchronization with high-speed sync (HSS) short shutter speeds, flash exposure compensation (FEC), second-curtain sync, and Multi-stroboscopic flash. Power control can be managed directly from the flash or via the Godox X system, and the easy-to-read LCD display makes it simple to quickly adjust settings while shooting.

Included in the set

- Godox V1 Canon Flash x1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- VB26 Lithium-Ion Battery x1
- Charger x1
- USB cable x1
- Carrying case x1
- Flash bracket x1
- User manual x1

Manufacturer	Godox
Model	V1 Canon
Compatibility	Canon
Power	76 Ws
Color Temperature	5600 K ±200 K
Flash Duration	1/350 – 1/20,000 s
Zoom	28-105 mm
Vertical Head Tilt	-7° to +120°
Horizontal head rotation	0° to 330°
Recycle time	Max. 1.5 s
Power supply	VB26 2,600 mAh lithium-ion battery
Capacity	Minimum 460 full flashes
Triggering	Hot shoe, test button, Godox X system
Power control	TTL, X system, via the flash unit
Operating modes	TTL, Multi, M, S1, S2, Master, Slave
HSS Synchronization	Yes
Multi-Flash Stroboscopic Mode	Yes
Groups/Channels	5 / 32
Display	LCD
Software Update	USB
Battery Pack Slot	No

Dimensions 7.6 × 9.3 × 19.7 cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

Weight

0.54 kg (with battery)

GPSR Link: <https://psr->[assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf](https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf), Box

length: 22,00, Box width: 19,50, Box height: 11,50, Gross weight: 980, Net weight: 958