

Hikvision Pro Series DS-2CD2066G2H-IU(2.8mm)(eF)/BLACK Indoor/Outdoor IP Security Bullet Camera 3200 x 1800 px Ceiling/Wall

Gamintojas: **HIKVISION** · Modelis: **DS-2CD2066G2H-IU** · EAN: **6942160480398** · Prekės kodas: **584702**



196,90 €

Kaina su PVM

Be PVM: **162,73 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Pixel counter: Yes | Bit rate range: 8 - 320 Kbit/s | Number of simultaneous live view channels: 6 channels | Lens viewing angle, diagonal: 143.5° | Sample rates: 8 - 48 kHz | Password reset via email: Yes | Lens viewing angle, horizontal: 114.8° | User access level: Administrator, Operator, User | Lens viewing angle, vertical: 60° | Frame rate: 30 fps | Fixed focal length: 2.8 mm | Digest authentication: Yes | Audio formats supported: G.722.1 | Sensor type: CMOS | IP address filtering: Yes | Audio formats supported: MP2L2 | Placement supported: Indoor & outdoor | Audio formats supported: G.726 | Progressive scan: Yes | DC output current: 0.58 A | Identify distance: 6 m | Recognize distance: 12 m | Signal-to-Noise Ratio (SNR): 52 dB | HTTPS encryption: Yes | Audio formats supported: AAC-LC | Detect distance: 64 m | Region of Interest (ROI) encoding: Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Video compression formats: H.264 | Built-in HDD: No | Number of users: 32 user(s) | DC output voltage: 12 | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Video compression formats: H.265 | Video compression formats: M-JPEG | Noise reduction: Yes | Video compression formats: H.264+ | Noise reduction technology: 3D noise reduction | Day/night mode: Yes | Maximum aperture number: 1 | Video compression formats: H.265+ | Observe distance: 25 m | Intelligent Video Surveillance (IVS) system features: Scene change | Intelligent Video Surveillance (IVS) system features: Vehicle detection | Intelligent Video Surveillance (IVS) system features: Region entrance detection | Mirror: Yes | Intelligent Video Surveillance (IVS) system features: Region exiting detection | Image quality adjustment: Brightness | Infrared (IR) cut-off filter: Yes | Password protection: Yes | Intelligent Video Surveillance (IVS) system features: Intrusion | Image quality adjustment: Saturation | Intelligent Video Surveillance (IVS) system features: Line crossing detection | Image quality adjustment: Contrast | Image quality adjustment: Sharpness | Intelligent Video Surveillance (IVS) system features: Human detection | Languages support: Multi | Heartbeat: Yes | Number of lenses: 1 | Night vision: Yes | Infra-red wavelength: 850 nm | Digital watermark: Yes | Dynamic range: 120 dB | Mounting type: Ceiling/wall | Active tampering alarm: Yes | Video

motion detection: Yes | Privacy masking: Yes | Bluetooth: No | Reset button: Yes | Weight: 505 g | LED type: IR | Compatible memory cards: MicroSDXC | Security algorithms: EAP-LEAP | Bit rate: 32 Kbps - 16 Mbps | Compatible memory cards: MicroSDHC | Connectivity technology: Wired | Security algorithms: TLS | Form factor: Bullet | Package width: 234 mm | Type: IP security camera | Compatible memory cards: MicroSD (TransFlash) | Maximum resolution: 3200 x 1800 pixels | International Protection (IP) code: IP67 | Camera shutter speed: 1/3 s - 1/100000 | Networking standards: IEEE 802.3af | Power consumption (max): 8.5 W | Total megapixels: 6 MP | Audio formats supported: G.711 | Audio formats supported: MP3 | Wi-Fi: No | Ethernet LAN: Yes | Angle of rotation: 360° | Audio formats supported: PCM | Depth: 179.2 mm | Security algorithms: EAP-MD5 | Package weight: 815 g | Ethernet interface type: Fast Ethernet | Storage relative humidity (H-H): 0 - 95% | Power source type: DC, PoE | Security algorithms: EAP-TLS | Number of cameras: 1 | Tilt angle range: 0 - 90° | Minimum illumination: 0 lx | Operating temperature (T-T): -30 - 60 °C | Diameter: 7.44 cm | Protection features: Water resistant | Operating relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.1x | Supported graphics resolutions: 640 x 480 (VGA) | Night vision distance: 40 m | Built-in microphone: Yes | Supported graphics resolutions: 640 x 360 | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Video formats supported: H.264+ | Package depth: 120 mm | Package height: 117 mm | Video formats supported: H.265+ | Wide Dynamic Range (WDR): Yes | Card reader integrated: Yes | Video formats supported: H.265 | Storage temperature (T-T): -30 - 60 °C | Protection features: Dust resistant | Supported graphics resolutions: 1280 x 720 (HD 720) | Housing material: Metal | Product colour: Black | Supported graphics resolutions: 3200 x 1800 | Pan range: 0 - 360° | Video formats supported: M-JPEG | Lens mount interface: M12 | Video formats supported: H.264 | Highlight Compensation (HLC): Yes | Compliance certificates: RoHS | Compliance certificates: KC | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: UKCA | Compliance certificates: Electromagnetic Compatibility (EMC) | Compliance certificates: CB | Compliance certificates: REACH | Number of Privacy masking areas: 4 | Audit log: Yes

Techninė specifikacija

Specifications	
Sandėlio grupė	Video cameras [+125][-110]
Matmenys ir svoris	
Matmenys (l × p × A)	24,00cm × 12,00cm × 13,00cm
Svoris	0,76kg