



**Hikvision Pro
Series DS-
2CD2066G2H-
IU(2.8mm)(eF)/BLACK
Indoor/Outdoor
IP Security
Bullet Camera
3200 x 1800 px
Ceiling/Wall**

Modelis: DS-2CD2066G2H-IU

Gamintojas: HIKVISION

EAN: 6942160480398

Prekės kodas: 584702

197.99€

Audio formats supported: G.722.1 | Intelligent Video Surveillance (IVS) system features: Line crossing detection | Noise reduction: Yes | Signal-to-Noise Ratio (SNR): 52 dB | Intelligent Video Surveillance (IVS) system features: Vehicle detection | Intelligent Video Surveillance (IVS) system features: Region entrance detection | Progressive scan: Yes | Number of simultaneous live view channels: 6 channels | Intelligent Video Surveillance (IVS) system features: Region exiting detection | Video compression formats: H.264 | Number of users: 32 user(s) | Intelligent Video Surveillance (IVS)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

system features: Intrusion | Maximum aperture number: 1 | Video compression formats: H.265+ | Intelligent Video Surveillance (IVS) system features: Human detection | Image quality adjustment: Saturation | Intelligent Video Surveillance (IVS) system features: Scene change | Image quality adjustment: Sharpness | Dynamic range: 120 dB | User access level: Administrator, Operator, User | Day/night mode: Yes | Video motion detection: Yes | Password protection: Yes | Image quality adjustment: Brightness | Mounting type: Ceiling/wall | Audio formats supported: AAC-LC | Audio formats supported: MP2L2 | Audio formats supported: G.726 | Frame rate: 30 fps | Video compression formats: M-JPEG | Image quality adjustment: Contrast | Password reset via email: Yes | Number of lenses: 1 | Video compression formats: H.265 | Built-in HDD: No | Identify distance: 6 m | Video compression formats: H.264+ | Noise reduction technology: 3D noise reduction | Pixel counter: Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Languages support: Multi | Infra-red wavelength: 850 nm | Detect distance: 64 m | Recognize distance: 12 m | DC output voltage: 12 | Sensor type: CMOS | Region of Interest (ROI) encoding: Yes | Active tampering alarm: Yes | IP address filtering: Yes | Infrared (IR) cut-off filter: Yes | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Heartbeat: Yes | Privacy masking: Yes | Observe distance: 25 m | DC output current: 0.58 A | HTTPS encryption: Yes | Mirror: Yes | Digital watermark: Yes | Fixed focal length: 2.8 mm | Night vision: Yes | Placement supported: Indoor & outdoor | Sample rates: 8 - 48 kHz | Lens viewing angle, vertical: 60° | Lens viewing angle, horizontal: 114.8° | Lens viewing angle, diagonal: 143.5° | Bit rate range: 8 - 320 Kbit/s | Digest authentication: Yes | Networking standards: IEEE 802.3af | Type: IP security camera | Ethernet LAN (RJ-45) ports: 1 | Security algorithms: EAP-MD5 | Connectivity technology: Wired | Security algorithms: EAP-TLS | Weight: 505 g | Supported graphics resolutions: 640 x 360 | Reset button: Yes | Security algorithms: EAP-LEAP | Networking standards: IEEE 802.1x | Product colour: Black | Security algorithms: TLS | Supported graphics resolutions: 2688 x 1520 | Package weight: 815 g | Maximum resolution: 3200 x 1800 pixels | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Tilt angle range: 0 - 90° | Bluetooth: No | Built-in microphone: Yes | Supported graphics resolutions: 3200 x 1800 | Supported graphics resolutions: 1280 x 720 (HD 720) | Power source type: DC, PoE | Supported graphics resolutions: 640 x 480 (VGA) | Compliance certificates: KC | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: UKCA | Compliance certificates: Electromagnetic Compatibility (EMC) | Compliance certificates: REACH | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: RoHS | Compliance certificates: CB | Audit log: Yes | Number of Privacy masking areas: 4 | Diameter: 7.44 cm | Storage temperature (T-T): -30 - 60 °C | Number of cameras: 1 | International Protection (IP) code: IP67 | Lens mount interface: M12 | Package height: 117 mm | Card reader integrated: Yes | LED type: IR | Pan range: 0 - 360° | Operating relative humidity (H-H): 0 - 95% | Highlight

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

Compensation (HLC): Yes | Night vision distance: 40 m | Ethernet LAN: Yes | Angle of rotation: 360° | Audio formats supported: PCM | Package depth: 120 mm | Audio formats supported: G.711 | Audio formats supported: MP3 | Depth: 179.2 mm | Wi-Fi: No | Form factor: Bullet | Package width: 234 mm | Ethernet interface type: Fast Ethernet | Minimum illumination: 0 lx | Back Light Compensation (BLC): Yes | Video formats supported: H.264+ | Video formats supported: H.264 | Compatible memory cards: MicroSDXC | Operating temperature (T-T): -30 - 60 °C | Video formats supported: H.265 | Compatible memory cards: MicroSD (TransFlash) | Housing material: Metal | Storage relative humidity (H-H): 0 - 95% | Video formats supported: H.265+ | Camera shutter speed: 1/3 s - 1/100000 | Compatible memory cards: MicroSDHC | Total megapixels: 6 MP | Bit rate: 32 Kbps - 16 Mbps | Power consumption (max): 8.5 W | Video formats supported: M-JPEG | Wide Dynamic Range (WDR): Yes | Protection features: Dust resistant | Protection features: Water resistant