



CyberPower OLS2000ERT2UA uninterruptible power supply (UPS) Double- conversion (Online) 2 kVA 1800 W 8 AC outlet(s)

Modelis: OLS2000ERT2UA

Gamintojas: CYBERPOWER

EAN: 4712856273816

Prekės kodas: 584859

581.99€

Certification: CE, EAC, RoHS | Input frequency: 50/60 Hz | Surge protection: Yes | Output frequency: 50/60 Hz | Efficiency (ECO mode): 95% | Audible alarm modes: Fault, Low battery alarm, Overload alarm | USB port: Yes | EMI/RFI noise filtering: Yes | Surge energy rating: 363 J | Typical backup time at half load: 13.1 min | ECO mode: Yes | Output voltage Total Harmonic Distortion (THD): 5% | Modem (RJ-11) ports: 1 | Display type: LCD | Maximum current: 9 A | Input power factor: 0.99 | Typical backup time at full load: 3.8 min | Waveform: Pure sine | Charging current: 1.5 A | Housing

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

material: Metal | Power protection features: Overload | Height: 88 mm | Non-operating altitude: 0 - 1500 m | UPS topology: Double-conversion (Online) | Harmonized System (HS) code: 8504408590 | Power factor: 0.9 | Audible alarm(s): Yes | Power plug: C14 coupler | Input operation voltage (min): 190 V | Hot-swap battery: Yes | Crest factor: 3:1 | Input operation voltage (max): 300 V | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Output power capacity: 2 kVA | AC outlet types: C13 coupler | Form factor: Rackmount/Tower | Operating relative humidity (H-H): 20 - 90% | Package height: 230 mm | Battery capacity: 9 Ah | Number of batteries supported: 4 | Noise level: 45 dB | Cables included: USB cable | AC outlets quantity: 8 AC outlet(s) | Battery voltage: 12 V | Package width: 540 mm | Storage relative humidity (H-H): 10 - 90% | Width: 438 mm | Output power: 1800 W | Response time: 0 ms | Ethernet LAN (RJ-45) ports: 1 | Battery technology: Sealed Lead Acid (VRLA) | Operating temperature (T-T): 0 - 40 °C | Depth: 430 mm | Weight: 17.1 kg | Storage temperature (T-T): -20 - 50 °C | Rack capacity: 2U | Operating altitude: 0 - 1500 m | Cable length: 1.5 m | Product colour: Black