



TP-Link 16-Port Gigabit Desktop Network Switch



Modelis: TL-SG116

Gamintojas: TP-LINK

EAN: 1210002616980

Prekės kodas: 584875

65.99€

AC input frequency: 50 Hz | Store-and-forward: Yes | Networking standards: IEEE 802.1Q | Operating temperature (T-T): 0 - 40 °C | MAC address table: 8000 entries | Auto-negotiation: Yes | Jumbo frames support: Yes | Packet buffer memory: 4.1 MB | Port mirroring: Yes | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | DC input voltage: 9 V | Storage relative humidity (H-H): 5 - 90% | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE): No | Width: 286 mm | Full duplex: Yes | Copper ethernet cabling technology: 100BASE-TX | 10G support: No | Cable types supported: Cat6 | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Cable types supported: Cat4 | Wall mountable: Yes | Height: 25.4 mm | Cable types supported: Cat3 | IGMP snooping: Yes | Broadcast storm control: Yes | Flow control support: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Quick start guide: Yes | Switching capacity: 32 Gbit/s | Link aggregation: Yes | Rate limiting: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Cable types supported: Cat5 | Cable types supported: Cat5e | Copper ethernet cabling technology: 10BASE-T | Depth: 111.7 mm | Product colour: Black | Copper ethernet cabling technology: 1000BASE-T | Power consumption

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(max): 9.3 W | Cables included: AC | Networking standards: IEEE 802.3u | Virtual LAN features: Protocol-based VLAN | Virtual LAN features: Tagged VLAN | Jumbo frames: 9000 | VLAN support: Yes | Housing material: Metal | Rack mounting: No | Forwarding rate: 23.81 Mpps | Auto MDI/MDI-X: Yes | AC input voltage: 220 V | Heat dissipation: 31.68 BTU/h | Number of queues: 4 | LED indicators: Yes | Switch type: Unmanaged | Cable length detection: Yes | Number of VLANs: 32 | Input current: 0.6 A | Loop protection: Yes