

Sharp MultiSync E659 Digital signage flat panel 165.1 cm (65") LCD 350 cd/m² 4K Ultra HD Black

Gamintojas: **SHARP** · Modelis: **PNE659** · EAN: **4550556167857** · Prekės kodas: **584956**



1 275,90 €

Kaina su PVM

Be PVM: **1 054,46 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment
- ✓ Standardised functionality – shares a common identity with the wider Sharp display portfolio, ensuring unified operation and remote device management, and consistent styling for a seamless user experience.
- ✓ Effortless plug-and-play signage – the integrated USB MediaPlayer enables native UHD content playback with auto-start functionality, delivering instant digital signage without the need for external hardware or content management systems.
- ✓ Flexible orientation – designed for both portrait and landscape installation, with uniform bezel width on all sides to ensure a clean, professional look in any configuration.



Aprašymas

Professional performance, affordable value

The entry point for professional display solutions, the Sharp MultiSync® E9 Series is designed for modern business environments that need more than a consumer TV can offer. Combining essential features for meeting rooms and digital signage with commercial-grade reliability, the E9 Series delivers crisp UHD resolution, integrated media playback, and 16/7 operation at an accessible price point. A professional matte high-haze panel ensures superior visual performance in this product category, minimising reflections and glare common with glossy panels.

Designed for seamless integration across the wider Sharp display family, the E9 Series shares the same core identity, including the same remote control and device management for a consistent user experience. A robust metal back cover secures product longevity in commercial settings. Whether for presentations, retail signage, or corporate communication, the E9 Series gives you the professional edge without stretching your budget

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Lcd Large Format [+107][-115]
Display	
Display diagonal	165.1 cm (65")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	350 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	IPS
LED backlight	Yes
LED backlighting type	Direct-LED
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.073 billion colours
Pixel pitch	0.372 x 0.372 mm
Active display area (W x H)	1428.48 x 803.52 mm
Display diagonal (metric)	164 cm
Horizontal scan range	31.5 - 135 kHz
Vertical scan range	24 - 75 Hz
Haze rate	25%
Ports & interfaces	
HDMI ports quantity	4
DVI port	No
DisplayPorts quantity	0
USB port	Yes
HDMI input ports quantity	2

HDMI output ports quantity	2
USB ports quantity	4
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)
USB connector type	USB Type-A, USB Type-C
Ethernet LAN (RJ-45) ports	1
PC Audio in	Yes
RS-232C	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Panel mounting interface	400 x 400 mm
Bezel width (bottom)	1.08 cm
Bezel width (side)	1.08 cm
Bezel width (top)	1.08 cm
Mounting type	Wall
Performance	
Purpose	Universal
Power	
Power consumption (typical)	125 W
Power consumption (standby)	2 W
Power consumption (sleep)	0.5 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	115 kWh
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Weight & dimensions	
Display width	1453 mm

Display depth	59.7 mm
Display height	829 mm
Display weight	16.5 kg
Packaging data	
Package width	1635 mm
Package depth	160 mm
Package height	987 mm
Package weight	23 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 80%
Network	
Ethernet LAN	Yes
Wi-Fi	No
Ethernet LAN data rates	100 Mbit/s
Matmenys ir svoris	
Matmenys (I × P × A)	163,00cm × 99,00cm × 16,00cm
Svoris	25,50kg