

Dahua Technology VTO2311R-WP video intercom system 2 MP Light grey

Gamintojas: **DAHUA** · Modelis: **VTO2311R-WP** · EAN: **6923172532534** · Prekės kodas: **585031**



147,90 €

Kaina su PVM

Be PVM: **122,23 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ultra slim design
- ✓ PC and ABS material make it ideal for indoor and outdoor use
- ✓ 1/2.8" 2-MP HD CMOS camera
- ✓ Offers two-way video call with indoor monitors
- ✓ Video and voice messages from visitors can be checked on the indoor monitor
- ✓ Video call and unlocking through app
- ✓ IR illumination and auto WDR
- ✓ Wi-Fi connection
- ✓ IP65 rated
- ✓ H.264 and H.265



Aprašymas

Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Operating temperature (T-T): -40 - 60 °C | Operating relative humidity (H-H): 10 - 90% | Ethernet interface type: Fast Ethernet | Maximum memory card size: 256 GB | Proper use: Outdoor | Ethernet LAN (RJ-45) ports: 1 | Built-in microphone: Yes | Night vision: Yes | RFID reader: Yes | Placement supported: Vertical | Touchscreen: Yes | Weight: 180 g | Wi-Fi standards: 802.11g | LED type: IR | Power consumption (standby): 3.5 W | Noise-canceling: Yes | Wall mountable: Yes | Depth: 30 mm | Cabling technology: 10/100Base-T(X) | Supported network protocols: RTSP, DNS, P2P, UPnP, RTP, RTMP, SIP, SSH, HTTP/HTTPS, ONVIF | Wi-Fi standards: Wi-Fi 4 (802.11n) | Sensor type: CMOS | Memory card slot: Yes | Fingerprint reader: Yes | Built-in speaker(s): Yes | Speakerphone: Yes | Wi-Fi: Yes | Viewing angle, vertical: 62° | Sustainability compliance: Yes | Ethernet LAN data rates: 10 | Supported video modes: 1080p | Video

formats supported: H.265 | Housing material: Acrylonitrile butadiene styrene (ABS) | Outdoor unit power type: DC | Supported video modes: 720p | Minimum order quantity: 1 pc(s) | Maximum frame rate: 30 fps | Colour: No | Control type: Touch | VoIP protocols: RTSP, DNS, P2P, UPnP, RTP, RTMP, SIP, SSH, HTTP/HTTPS, ONVIF | Housing material: Polycarbonate (PC) | Video formats supported: H.264 | Voice codecs: G.711u | Height: 160 mm | Package weight: 400 g | AC adapter output voltage: 33 V | Compatible memory cards: SD | Wi-Fi standards: 802.11b | Automatic gain control: Yes | Power over Ethernet (PoE): Yes | Voice codecs: G.711a | Compatible memory cards: MicroSD (TransFlash) | AC adapter output current: 1 A | Maximum number of cameras supported: 1 | Width: 50 mm | Voice codecs: PCM | Quantity per pack: 1 pc(s) | Door station control: Yes | Optical sensor size: 25.4 / 2.8 mm (1 / 2.8") | Ethernet LAN data rates: 100 Mbit/s | Viewing angle, horizontal: 110° | Outdoor unit included: Yes | Power consumption (typical): 6 W | Megapixel (approx.): 2 MP | International Protection (IP) code: IP65 | Motion detection function: Yes | Connectivity technology: Wireless | Product colour: Light grey

Techninė specifikacija

Specifications	
Sandėlio grupė	Intercoms [+4][-7]
Features	
Connectivity technology	Wireless
Colour	No
Maximum number of cameras supported	1
Speakerphone	Yes
RFID reader	Yes
Fingerprint reader	Yes
Door station control	Yes
VoIP protocols	RTSP, DNS, P2P, UPnP, RTP, RTMP, SIP, SSH, HTTP/HTTPS, ONVIF
Wall mountable	Yes
Built-in microphone	Yes
Automatic gain control	Yes
Motion detection function	Yes
Display	
Touchscreen	Yes
Video formats supported	H.264, H.265
Camera	
Megapixel (approx.)	2 MP
Supported video modes	720p, 1080p
Sensor type	CMOS
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Maximum frame rate	30 fps
Viewing angle, horizontal	110°
Viewing angle, vertical	62°

Night vision

Night vision	Yes
LED type	IR

Audio

Built-in speaker(s)	Yes
Noise-canceling	Yes
Voice codecs	G.711a, G.711u, PCM

Design

Product colour	Light grey
International Protection (IP) code	IP65
Housing material	Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)
Control type	Touch
Placement supported	Vertical
Proper use	Outdoor

Storage

Memory card slot	Yes
Compatible memory cards	MicroSD (TransFlash), SD
Maximum memory card size	256 GB

Network

Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Ethernet LAN (RJ-45) ports	1
Wi-Fi	Yes
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Cabling technology	10/100Base-T(X)
Power over Ethernet (PoE)	Yes
Supported network protocols	RTSP, DNS, P2P, UPnP, RTP, RTMP, SIP, SSH, HTTP/HTTPS, ONVIF

Power

Outdoor unit power type	DC
AC adapter output voltage	33 V
AC adapter output current	1 A
Power consumption (typical)	6 W
Power consumption (standby)	3.5 W

Operational conditions

Operating temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	50 mm
Depth	30 mm
Height	160 mm
Weight	180 g
Packaging data	
Outdoor unit included	Yes
Package weight	400 g
Technical details	
Compliance certificates	CE, Federal Communications Commission (FCC)
Sustainability compliance	Yes
Logistics data	
Quantity per pack	1 pc(s)
Minimum order quantity	1 pc(s)
Matmenys ir svoris	
Matmenys (I × P × A)	11,00cm × 12,00cm × 21,00cm
Svoris	0,47kg