



Cudy AP11000 wireless access point 10777 Mbit/s White Power over Ethernet (PoE)



Modelis: AP11000 1.0

Gamintojas: CUDY

EAN: 6971690793586

Prekės kodas: 585124

171.99€

Bundled software: 1 | 2.4 GHz: Yes | Mounting kit: Yes | VLAN support: Yes | Flash memory: 128 MB | Reset button: Yes | 5 GHz: Yes | Security algorithms: WPA3 | Interface: 2 | AC adapter included: No | WAN connection: Ethernet (RJ-45) | Width: 231.9 mm | Placement: Ceiling, Wall | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Internal memory: 512 MB | MIMO type: Multi User MIMO | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Storage relative humidity (H-H): 5 - 95% | WAN connection: SFP+ | Networking standards: IEEE 802.11be | Security algorithms: WPA2 | IGMP snooping: Yes | Package depth: 238 mm | Product colour: White | Networking standards: IEEE 802.11b | Maximum data transfer rate: 10777 Mbit/s | Ethernet LAN data rates: 2500 | Package width: 310 mm | Package height: 73 mm | MAC address filtering: Yes | Depth: 57.1 mm | DC-in jack: Yes | Output voltage: 12 V | Power over Ethernet (PoE): Yes | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Antenna type:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Internal | Package weight: 944 g | Height: 231.9 mm | Cables included: LAN (RJ-45) | Processor frequency: 1500 MHz | Power consumption (max): 20 W | Maximum data transfer rate (2.4 GHz): 688 Mbit/s | Ethernet LAN (RJ-45) ports: 1 | Products per shipping (inner) case: 10 pc(s) | Operating temperature (T-T): 0 - 40 °C | DHCP client: Yes | Antennas quantity: 6 | Quick start guide: Yes | Antenna gain level (max): 5.8 dBi | Power consumption (typical): 12 W | Output current: 2 A | LED indicators: System | Weight: 578.2 g | Maximum outdoor range: 260 m | Maximum data transfer rate (5 GHz): 4320 Mbit/s | Operating relative humidity (H-H): 10 - 90% | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Virtual LAN features: Tagged VLAN | PoE adapter included: No | DC voltage range: 48-57 V | Syslog: Yes | Cloud-managed: Yes | SFP/SFP+ slots quantity: 1 | Power over Ethernet (PoE) type supported: Passive PoE | Warranty period: 1 year(s) | Maximum data transfer rate (6 GHz): 5760 Mbit/s | BeamForming: Yes | 6 GHz: Yes