

Cudy AP11000 wireless access point 10777 Mbit/s White Power over Ethernet (PoE)

Gamintojas: CUDY · Modelis: AP11000 1.0 · EAN: 6971690793586 · Prekės kodas: 585124



145,90 €

Kaina su PVM

Be PVM: 120,58 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Qualcomm 1.5 GHz Quad-Core CPU
- ✓ 6-Stream Tri-Band Wi-Fi 7
- ✓ 5.7 Gbps + 4.3 Gbps + 688 Mbps
- ✓ 1× 10G SFP, 1× 2.5GbE PoE IN
- ✓ 802.3at, Passive PoE, DC
- ✓ Multi-AP Management
- ✓ Captive Portal, Multi-SSID
- ✓ Watchdog, Schedule Reboot
- ✓ Covers 140 m² (1,500 ft²)
- ✓ 300 Connected Devices



Aprašymas

Pristine 6 GHz for Business-Grade Connectivity

The expanded 6 GHz band offers up to 2.4× more channels than 5 GHz, allowing the AP11000 to deliver unprecedented speeds and handle more client devices in interference-free environments. Perfect for high-density business environments.

Ultra-Performance 10G SFP+ Fiber Uplink

With 10G SFP+ uplink support, AP11000 goes beyond the limits of standard Gigabit connections, ensuring high-throughput, low-latency fiber connectivity and offering a reliable, future-proof solution for enterprise and commercial networks.

Seamless Wi-Fi for Everywhere

Campus

Hospitality

Conference Center

Shopping Mall

Advanced Business Features

Captive Portal

Improve your brand awareness by displaying a customized login page for new clients.

Band Steering

Assign devices to less congested bands.

Auto Channel Selection

Avoid signal interruptions with nearby access points.

Auto Mesh Optimization

Form mesh backhaul via less congested routes automatically.

Versatile Powering and Installation

Flexible PoE/DC Power Options

12V/2A DC

802.3at

48-57V Passive PoE

Please note: DC adapter is not included in the package.

Versatile Mounting

Ceiling Mounting

Wall Mounting

Mounting kits are included in the box.

Centralized AP Management

Easily manage up to 200 access points with Cudy AP Controller Model:C200P , enabling efficient batch configuration and firmware updates through a unified interface.

Techninė specifikacija

Specifications	
Sandėlio grupė	AccesPoint [+40][-26]
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	Yes

Maximum data transfer rate	10777 Mbit/s
Maximum data transfer rate (2.4 GHz)	688 Mbit/s
Maximum data transfer rate (5 GHz)	4320 Mbit/s
Maximum data transfer rate (6 GHz)	5760 Mbit/s
Ethernet LAN data rates	2500 Mbit/s
Networking standards	IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n, IEEE 802.11b
MIMO	Yes
MIMO type	Multi User MIMO
VLAN support	Yes
Virtual LAN features	Tagged VLAN
BeamForming	Yes
Maximum outdoor range	260 m
Security	
Security algorithms	WPA, WPA2, WPA3
MAC address filtering	Yes
IGMP snooping	Yes
Protocols	
DHCP client	Yes
Management features	
Syslog	Yes
Cloud-managed	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	0
Interface	2
SFP/SFP+ slots quantity	1
WAN connection	SFP+, Ethernet (RJ-45)
DC-in jack	Yes
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
DC voltage range	48-57 V
Output voltage	12 V
Output current	2 A

Power consumption (typical)	12 W
Power consumption (max)	20 W
Design	
Placement	Ceiling, Wall
Product colour	White
Reset button	Yes
LED indicators	System
Antenna	
Antenna type	Internal
Antennas quantity	6
Antenna gain level (max)	5.8 dBi
Performance	
Processor frequency	1500 MHz
Flash memory	128 MB
Internal memory	512 MB
Technical details	
Products per shipping (inner) case	10 pc(s)
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Weight & dimensions	
Width	231.9 mm
Depth	57.1 mm
Height	231.9 mm
Weight	578.2 g
Packaging data	
Package width	310 mm
Package depth	238 mm
Package height	73 mm
Package weight	944 g
Packaging content	
AC adapter included	No
PoE adapter included	No
Cables included	LAN (RJ-45)
Mounting kit	Yes

Quick start guide	Yes
Bundled software	1
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 95%
Logistics data	
Warranty period	1 year(s)
Country of origin	China
Matmenys ir svoris	
Matmenys (I × P × A)	7,00cm × 31,00cm × 24,00cm
Svoris	1,04kg