

Bezobsługowe zarządzanie

Zarządzaj urządzeniami zdalnie za pośrednictwem Poly Lens⁴.



HP Thunderbolt 4 Ultra 280W G6 Dock



Modelis: AW5M5UT

Gamintojas: HEWLETT-PACKARD

EAN: 198701752547

Prekės kodas: 585314

275.99€

Box contents: HP Thunderbolt 4 Ultra 280W G6 Dock 330 W power adapter Thunderbolt 4 and 4.5 mm power barrel combination cable (1 m) Power cord Product notice Warranty card | Compatibility: Tested and supported on select HP commercial PCs. For HP notebook compatibility please visit - <https://pcb.inc.hp.com/webapp/!us-en> and search by notebook. Tested and supported on select 3rd party PCs. Contact your local sales representative to learn more. | Special features: Intel vPro support | Bundled software: Poly Lens with automatic firmware updates | Compatible operating systems: Windows 10 Windows 11 macOS Linux ThinPro ChromeOS | HP GTIN (EAN/UPC): 195161448027, 195161448034, 195161269653, 195161448058 | Sustainable technologies and materials: 35% post-consumer recycled plastic | Thunderbolt 4 ports quantity: 1 | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 Mbit/s | Connectivity technology: Wired | Mac operating systems supported: MacOS | Ethernet LAN data rates: 2500 | Ethernet LAN: Yes | Package depth: 171 mm | HDMI version: 2.1 | Microphone in: No | Width: 121 mm | Ethernet LAN data rates: 100 | HD type: 8K Ultra HD | Storage temperature (T-T): -20 - 60 °C | Product colour: Grey | Host interface: Thunderbolt 4 | DisplayPort version: 1.4 | Height: 49.5 mm | HDMI ports quantity: 1 | Master (outer) cases per pallet layer: 28 pc(s) | Weight: 790 g | Package weight: 1.14 kg | Storage relative humidity

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(H-H): 5 - 95% | Card reader integrated: No | Package height: 95 mm | DisplayPorts quantity: 2 | HP segment: Business | Pallet dimensions (W x D x H) (imperial): 1199.9 x 1000 x 140 mm (47.2 x 39.4 x 5.51") | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 1 | Windows operating systems supported: Windows 10 | Cables included: AC | Maximum refresh rate: 360 Hz | Cable lock slot type: Nano | Package width: 396 mm | Warranty card: Yes | Other operating systems supported: ChromeOS | UNSPSC-code: 43211602 | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): 0 - 35 °C | Pallet dimensions (W x D x H): 1200 x 1000 x 140 mm | Operating relative humidity (H-H): 10 - 90% | USB Power Delivery up to: 280 W | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 3 | Power supply: 330 W | Windows operating systems supported: Windows 11 | Depth: 121 mm | USB Power Delivery (USB PD): Yes | LED indicators: Power | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | Operating altitude: -15 - 3048 m | Cable lock slot: Yes | Non-operating altitude: -15 - 12192 m | Linux operating systems supported: Yes | Total carbon footprint (kg of CO2e): 6.3 | General Product Safety Regulation (GPSR) URL: https://kaas.hpcloud.hp.com/pdf-public/pdf_11069394_en-US-1.pdf | Carbon emissions, end-of-life (kg of CO2e): 11 | Carbon emissions, logistics (kg of CO2e): 3 | Carbon emissions, manufacturing (kg of CO2e): 74 | Total carbon emissions, w/o use phase (kg of CO2e): 14