

HIKVISION DS-2SE4C425MWG-E/26(F0) IP Camera

Gamintojas: **HIKVISION** · Modelis: **DS-2SE4C425MWG-E/26(F0)** · EAN: **6931847199630** · Prekės kodas: **585338**



547,90 €

Kaina su PVM

Be PVM: **452,81 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

Ethernet LAN: Yes | Weight: 2.4 kg | Tilt angle range: 0 - 90° | Power consumption (max): 24 W | Power source type: PoE+, DC | Type: IP security camera | Card reader integrated: Yes | Supported graphics resolutions: 352 x 288 | Compatible memory cards: MicroSDHC | Supported graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 960 x 432 | Supported graphics resolutions: 704 x 480 | Wide Dynamic Range (WDR): Yes | Product colour: White | Height: 375 mm | Quality of Service (QoS) support: Yes | Product colour: Black | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): -30 - 65 °C | Maximum resolution: 3632 x 1632 pixels | Bit rate: 32 Kbps - 16 Mbps | Operating relative humidity (H-H): 0 - 90% | Ethernet interface type: Fast Ethernet | Compatible memory cards: MicroSDXC | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 1200 x 536 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 3632 x 1632 | Connectivity technology: Wired | Supported graphics resolutions: 352 x 240 | Protection features: Waterproof | Supported graphics resolutions: 640 x 480 (VGA) | Compatible memory cards: MicroSD (TransFlash) | Supported graphics resolutions: 1280 x 720 (HD 720) | International Protection (IP) code: IP66 | Zoom speed: 3.6 s | Number of cameras: 1 | Lens viewing angle, vertical: 33 - 1.4° | Zoom capability: Yes | Product diameter: 166 mm | Camera shutter speed: 1 - 1/30000 s | Supported network protocols: IPv4/IPv6, HTTP, HTTPS, QoS, 802.1x, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP/IP, DHCP, PPPoE, Bonjour | Frame rate: 25 / 30 fps | Built-in speaker(s): Yes | Alarm input channels: 1 | Minimum illumination: 0 lx | Auto focus: Yes | Night vision: Yes | Number of users: 32 user(s) | IP address filtering: Yes | Region of Interest (ROI) encoding: Yes | Live view: Yes | LED type: IR | Maximum memory card size: 256 GB | Audio formats supported: MP3 | Client interoperability: iVMS-4200, Hik-Connect | Preset programs quantity: 300 | Audio formats supported: AAC-LC | Audio formats supported: G.722.1 | Sensor type: CMOS | Progressive scan: Yes | Pan range: 360 | Alarm output channels: 1 | Digital watermark: Yes | Video motion detection: Yes | Audio formats supported: MP2L2 | Audio formats supported: PCM | Video compression formats: H.264 | Video compression formats: M-JPEG | Optical zoom: 25x | PTZ control: Yes | Automatic Network Replenishment (ANR): Yes | Day/night mode: Yes | Number of simultaneous live view channels: 20 channels | Video compression formats: H.265 | Audio formats supported: G.726 | Total megapixels: 6 MP | Placement supported: Outdoor | Alarm input/output: Yes | Privacy masking: Yes | DC output voltage: 12 | Digital zoom: 16x | Password protection: Yes | PTZ status display: Yes | Audio formats supported: G.711 | Dynamic range: 120 dB | Lens viewing angle, diagonal: 61.5 - 2.8° | Mounting type: Ceiling | Highlight Compensation (HLC): Yes | Lens viewing angle, horizontal: 55 - 2.4°

Techninė specifikacija

Specifications

Sandėlio grupė	Video cameras [+125][-111]
----------------	----------------------------

Matmenys ir svoris

Matmenys (l × p × A)	22,00cm × 30,00cm × 55,00cm
----------------------	-----------------------------

Svoris	5,05kg
--------	--------