ASUS PRIME Z790M-PLUS Intel Z790 LGA 1700 „micro ATX“

Gamintojas: **ASUS** · Modelis: **90MB1E70-M0EAY0** · EAN: **4711387025741** · Prekės kodas: **586320**

215,90 €

Kaina su PVM

Be PVM: **178,43 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intel LGA 1700 „Intel® Celeron®“, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium® Gold
- ✓ PC „micro ATX“ Intel Z790 7.1 kanalai
- ✓ DDR5-SDRAM 4 DIMM Maksimali vidinė atmintis: 128 GB
- ✓ HDD & SSD M.2, PCI Express 4.0, SATA RAID palaikymas Palaikomų saugojimo tvarkyklių skaičius: 4
- ✓ BIOS tipas: UEFI AMI 192 Mbit
- ✓ Gigabitinis eternetas

Aprašymas

ASUS Prime series motherboards are expertly engineered to unleash the full potential of 13th Gen Intel® Core™ Processors. Boasting a robust power design, comprehensive cooling solutions and intelligent tuning options, PRIME Z790M-PLUS provides users and PC DIY builders with a range of performance optimizations via intuitive software and firmware features.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

FLEXIBILITY

Comprehensive controls form the foundation of the ASUS PRIME series. The PRIME Z790M-PLUS motherboard packs flexible tools to tune every aspect of your system, enabling performance tweaks to perfectly match the way you work to maximize productivity.

Intelligent Control

ASUS Intelligent Control makes your PC smart. Along with taking care of complex tuning and dynamically optimizing essential aspects of your system, it offers intelligently simplified options for newcomers to PC DIY, as well as more comprehensive features for seasoned veterans.

All-Around Energy Efficiency

The Power Saving function contains several settings can easily optimize power consumption and maximize energy savings. You can enable a CPU power limit, darken Aura lighting, and set the fan profile to a power saving mode. You can also toggle the Power Saver plan that is built into Microsoft Windows.

Flexible Air- and Liquid-Cooling Controls

ASUS Fan Xpert 4 software provides comprehensive control over fans, water pumps and all-in-one (AIO) coolers. Whether cooling with air or water, an Auto-Tuning mode intelligently configures all parameters with a single click. There’s also an Extreme Quiet mode that reduces all fan speeds to below the default minimum to keep your system whisper-quiet when performing light tasks. Fans, water pumps and AIO coolers can also be controlled via the UEFI BIOS.

Precise Digital Power Control

The Digi+ voltage-regulator module (VRM) delivers real-time control over voltage droop, automatically switching frequency and power-efficiency settings. It also allows you to fine-tune your CPU for ultimate stability and performance.

AI Cooling II

AI Cooling II balances the thermals and acoustics of any build with a single click. A proprietary ASUS algorithm slashes unnecessary noise while running a quick stress test, and then it monitors CPU temperatures to dynamically adjust fans to optimal speeds.

Advanced Tuning for Serious Tweakers

An intuitive Advanced mode offered via the UEFI lets you take complete control. A built-in search feature makes it easy to find options, and various advanced functions let you intelligently make nuanced adjustments so you can dial in performance just the way you want.

Search Function

Quickly and easily find the option or setting you need.

ASUS User Profile

Port configuration settings between different BIOS versions or share them with friends.

COOLING

PRIME Z790M-PLUS motherboard is engineered with multiple onboard heatsinks and an array of hybrid fan headers to ensure your rig stays cool and stable under intense workloads.

VRM Heatsinks and Thermal Pads

The extensive surface area of the massive heatsinks cover the VRMs and chokes to improve heat dissipation. Together with specially engineered thermal pads, they improve heat transfer from the MOSFETs and chokes for better cooling performance.

Cooler by Design

PRIME Z790M-PLUS features comprehensive cooling controls that are configurable via Fan Xpert 4 software or via the UEFI BIOS.

Multiple Temperature Sources

Each header can dynamically reference three thermal sensors. Fan Xpert 4 allows you to map the temperature of supported ASUS graphics cards to optimize cooling for GPU- and CPU-intensive tasks.

AIO Pump Header

A dedicated PWM/DC header for self-contained water-cooling setups.

Smart Protection

A dedicated integrated circuit protects each fan header from overheating and overcurrent

4-Pin PWM/DC Fan

Each onboard header supports auto-detection of PWM or DC fans

PERFORMANCE

The PRIME Z790M-PLUS motherboard is built to handle the high core counts and bandwidth demands of 13th Gen Intel® Core™ Processors. ASUS Z790 motherboard provides all the fundamentals to boost daily productivity, so your system will be ready for action with stable power, intuitive cooling and flexible data transfer options.

Robust Power Design

Stable power is essential to extract every last bit of performance out of Intel processors. The PRIME Z790M-PLUS is geared to cater to the demands of these high-core-count CPUs.

AEMP II for Ultimate DDR5 Performance

ASUS Enhanced Memory Profile II (AEMP II) is an exclusive firmware feature for PMIC-restricted memory modules. AEMP II is based on a CPU and memory module’s ability to train the memory chips on your kit, and it presents an optimized clock speed that can effortlessly unleash performance.

Built through a flexible training method, AEMP II makes it easy to not only tune the memory above baseline settings but also maintain the stability of system operation, whether getting the most out of an entry-level module or priming a high-speed kit for ultimate performance.

ASUS OptiMem II

Revisions to the motherboard’s trace routing provide the latest Intel® processors with unrestricted access to memory bandwidth. ASUS OptiMem II technology carefully maps memory signal pathways across different PCB layers to reduce vias and adds shielding zones that significantly reduce crosstalk.

Benefits of ASUS OptiMem II:

Improved memory stability and compatibility
Allows lower memory latencies at equivalent voltages
Improved memory frequency margin

Outstanding Audio
Combined onboard features deliver elevated audio

Intelligent design and premium hardware create audio quality unlike anything you’ve ever experienced.
Audio Shielding

Audio shielding ensures precision analog/digital separation and greatly reduced multi-lateral interference.
Dedicated Audio PCB Layers

Separate layers for left and right tracks ensures both channels deliver consistent, equal quality.
Premium Audio Capacitors

Provides warm, natural, and immersive sound with exceptional clarity and fidelity.

Aura Sync

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Outshine the Competition

A well-tuned enthusiast system deserves a matching aesthetic. ASUS Aura offers full RGB lighting control with a variety of functional presets for the built-in RGB LEDs as well as strips and devices connected to the onboard RGB headers — and it can all be synced with an ever-growing portfolio of Aura-capable hardware.

Q-LED Core

The Q-LED Core display produces light patterns by power LED during the Power-On Self-Test (POST) that can help users troubleshoot potential issues.

Techninė specifikacija

Procesorius	
Procesoriaus gamintojas	Intel
Procesoriaus lizdas	LGA 1700
Procesorių suderinamumas	„Intel® Celeron®“, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium® Gold
Atmintis	
Palaikomi atminties tipai	DDR5-SDRAM
Atminties angų skaičius	4
Maksimali vidinė atmintis	128 GB
Atminties angų tipas	DIMM
Atminties kanalai	Dviejų kanalų
ECC suderinamumas	Ne-ECC
Palaikomi atminties laikrodžio greičiai	4800,5000,5200,5400,5600,5800,6000,6200,6400,6600,6800,7000,7200 MHz
Nebuferizuota atmintis	Taip
Duomenų laikymo valdikliai	
Palaikomi saugojimo kaupiklių sąsajos	M.2, PCI Express 4.0, SATA
Palaikomi saugojimo kaupiklių tipai	HDD & SSD
Palaikomų kietųjų diskų skaičius	3
Palaikomų saugojimo tvarkyklių skaičius	4
RAID palaikymas	Taip
RAID lygiai	0, 1, 5, 10
Grafika	
Integruotas grafikos adapteris	Ne
Vidinis I/O	
USB 2.0 jungtys	2
USB 3.2 (3.1 1 kart.) jungtys	2

USB 3.2 (3.1 2 kart.) jungtys	0
SATA III jungčių skaičius	4
SATA II jungčių skaičius	0
SATA jungčių skaičius	0
S/PDIF out jungtis	Taip
Garso jungtis	Taip
ATX maitinimo jungtis	Taip
Galios ventiliatorių jungtis	Taip
CPU fan jungtis	Taip
Šasi fenų jungčių skaičius	3
Periferinė (Molex) galios jungtis (4-pin)	1
EPS maitinimo jungtis (8-kaisčiai)	Taip
COM jungčių skaičius	1
Nuosekliojo prievado antraštės	1
„Thunderbolt“ kolektoriai	1
12 V maitinimo jungtis	Taip
RGB LED kontaktų pagrindas	Taip
Galinė panelė I/O jungtys	
USB 2.0 portų kiekis	4
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	4
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius	1
USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius	0
Ethernet LAN (RJ-45) portų kiekis	1
VGA (D-Sub) portų kiekis	0
HDMI portų kiekis	1
DVI-D prievadų skaičius	0
USB 3.2 Gen 2x2 C tipo prievadų kiekis	1
HDMI versija	2.0
„DisplayPort“ kiekis	1
„DisplayPort“ versija	1.4
Ausinių išvestys	1
Įvedimas	Taip
Mikrofonas, line-in jack	Taip
COM portų kiekis	1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

USB jungtis	USB A tipo
Tinklas	
„Wi-Fi“	Ne
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	Gigabitinis eternetas
Savybės	
Taikoma	PC
Motininės plokštės formos faktorius	„micro ATX“
Motininės plokštės sisteminio valdiklio šeima	Intel
Pagrindinės plokštės lustas	Intel Z790
Garso išvesties kanalai	7.1 kanalai
Produkto spalva	Aliuminis, Juoda
Maitinimo šaltinio tipas	ATX
Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 11
Plėtotės lizdas	
„PCI Express x1 (Gen 4.x)“ lizdai	2
„PCI Express x16“ (4 kartos) lizdai	1
„PCI Express x16“ („Gen 5.x“) lizdai	1
M.2 (M) angų skaičius	3
BIOS	
BIOS tipas	UEFI AMI
BIOS atminties dydis	192 Mbit
Svoris ir matmenys	
Plotis	244 mm
Ilgis	244 mm
Pakuotės turinys	
Pridėti kabeliai	SATA
Siejama programinė įranga	ASUS Exclusive Software Armoury Crate - Aura Sync - Fan Xpert 4 (with AI Cooling II) - Power Saving AI Suite 3 - TurboV EVO - DIGI+ VRM - PC Cleaner ASUS CPU-Z Norton 360 Deluxe (60 Days Free Trial) WinRAR UEFI BIOS ASUS EZ DIY - ASUS CrashFree BIOS 3 - ASUS EZ Flash 3 - ASUS UEFI BIOS EZ Mode
Kitos savybės	
mSATA prievadų skaičius	0
Matmenys ir svoris	
Svoris	1,30kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc
Li-Te Road 15, 112 Taipei, TW
asus.com

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.
Allee bienvenue 10, 93160 Paris, FR
channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt