

AG Neovo IFP8604P interactive whiteboard 2.18 m (86") 3840 x 2160 pixels Touchscreen

Gamintojas: **AG NEOVO** · Modelis: **IF864011G0000** · EAN: **4710739598483** · Prekės kodas: **587228**



2 945,90 €

Kaina su PVM

Be PVM: **2 434,63 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Touchscreen 2.18 m (86") IPS
- ✓ 4K Ultra HD 3840 x 2160 pixels
- ✓ 400 cd/m² 1200:1 5 ms
- ✓ Built-in speaker(s) 30 W Built-in microphone
- ✓ Wi-Fi 6 (802.11ax) Bluetooth Ethernet LAN
- ✓ VESA mounting 800 x 600 mm
- ✓ 350 W



Aprašymas

AG Neovo IFP8604P. Bildschirmdiagonale: 2,18 m (86"), Helligkeit: 400 cd/m², Anzahl der Farben des Displays: 1,07 Milliarden Farben. Installiertes Betriebssystem: Android, RAM-Speicher maximal: 8 GB, Benutzerspeicher: 128 GB. Lautsprecherleistung: 30 W. Kamera-Auflösung (numerisch): 8 MP. Top WLAN-Standard: Wi-Fi 6 (802.11ax)

Techninė specifikacija

Specifications

Sandėlio grupė

Large Format Displays [+0][-0]

Display

Display diagonal	2.18 m (86")
Touchscreen	Yes
Display brightness	400 cd/m²
Display number of colours	1.07 billion colours
Display resolution	3840 x 2160 pixels
Anti-glare screen	Yes
HD type	4K Ultra HD
Panel type	IPS
Contrast ratio (typical)	1200:1
Response time	5 ms
Touch technology	Multi-touch
Touchscreen type	Infrared
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.494 x 0.494 mm
Screen glass thickness	3.2 mm
Haze rate	25%
Hardness	3H
Accuracy touch	1 mm

Computer system

Operating system installed	Android
Operating system version	13
Maximum internal memory	8 GB
User memory	128 GB
RAM capacity	8 GB

Audio

Built-in speaker(s)	Yes
Number of built-in speakers	2
Speaker power	30 W
Built-in microphone	Yes
Number of microphone arrays	8

Camera

Built-in camera	Yes
-----------------	-----

Camera resolution (numeric)	8 MP
Projector	
Built-in projector	No
Network	
Wi-Fi	Yes
Top Wi-Fi standard	Wi-Fi 6 (802.11ax)
Bluetooth	Yes
Ethernet LAN	Yes
Ports & interfaces	
HDMI ports quantity	2
USB Type-C ports quantity	1
HDMI version	2.1
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	60 W
Ethernet LAN (RJ-45) ports	2
S/DPDIF out port	Yes
RS-232 ports	1
Ergonomics	
VESA mounting	Yes
Panel mounting interface	800 x 600 mm
Power	
Power consumption (max)	350 W
Power consumption (standby)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
System requirements	
Windows operating systems supported	Windows 10, Windows 11, Windows 2000, Windows 7, Windows 8, Windows CE, Windows Vista, Windows XP
Mac compatibility	Yes
Mac operating systems supported	MacOS
Linux operating systems supported	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%

Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 80%
Weight & dimensions	
Width	1961.8 mm
Height	1200.9 mm
Depth	123.9 mm
Weight	72 kg
Packaging data	
Package width	2160 mm
Package depth	225 mm
Package height	1310 mm
Package weight	81.4 kg
Quantity per pack	1 pc(s)
Packaging content	
Manual	Yes
Cables included	AC, HDMI, USB
Remote control included	Yes
Batteries included	Yes
Quick start guide	Yes
Stylus included	Yes
Open Pluggable Specification (OPS) included	Yes
Sustainability	
Compliance certificates	CE, EAC, Low Voltage Directive (LVD), REACH, RoHS
Certificates	
Waste Electrical and Electronic Equipment (WEEE) compliance	Yes
Matmenys ir svoris	
Matmenys (l × P × A)	216,00cm × 132,00cm × 23,00cm
Svoris	84,00kg