

GIGABYTE Gen4 4000E 500 GB M.2 PCI Express 4.0 NVMe 3D NAND

Gamintojas: **GIGABYTE** · Modelis: **G440E500G** · EAN: **4719331860042** · Prekės kodas: **589137**



122,90 €

Kaina su PVM

Be PVM: **101,57 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Form Factor: M.2 2280
- ✓ Interface: PCI-Express 4.0 x4, NVMe 1.4
- ✓ Total Capacity: 500GB
- ✓ Sequential Read Speed : up to 3600 MB/s
- ✓ Sequential Write speed : up to 3000 MB/s
- ✓ HMB (Host Memory Buffer) supported
- ✓ TRIM & S.M.A.R.T support
- ✓ Energy-Efficient



Aprašymas

The Benefits of upgrading to PCIe Gen4.0 x4 SSDs

Here are 3 key benefits for those looking to upgrade their PC with PCIe 4.0 x4 SSDs.

1. Motherboard support PCIe 4.0 x4 SSD becomes mainstream

Many motherboards support the PCIe 4.0 x4 M.2 slot, from Intel Z490 to AMD X570 and beyond. With the widespread adoption of the PCIe 4.0 x4 M.2 slot in motherboards, upgrading your computer for greater efficiency has become easier. The GIGABYTE Gen4 4000E SSD is the first choice when it comes to boosting performance.

2. Improved performance for users

The performance boost offered by PCIe 4.0 x4 SSDs goes beyond gaming. For power users who are busy with data processing, file transfers and multitasking, the higher bandwidth of PCIe 4.0 significantly improves the overall performance of the PC. Whether you're managing large data sets or handling intensive tasks, PCIe 4.0 provides a smoother and more responsive user experience.

3. Faster operating system speed

The increased bandwidth of PCIe 4.0 SSDs results in a faster operating system. Expect instant boot times and fast loading of programmes when using Windows OS. This improvement in everyday usability enhances the overall user experience.

Unleash the Power of PCIe 4.0 x4 and NVMe 1.4

Boasting a PCIe 4.0 x4 interface and adhering to the NVMe 1.4 specification, GIGABYTE Gen4 4000E SSD offers a sequential read speed of up to 3,600 MB/s and a sequential write speed of 3,000 MB/s. Whether you're gaming, creating content, or handling large files, GIGABYTE Gen4 4000E SSD ensures swift and seamless operations.

Host Memory Buffer (HMB)

The Host Memory Buffer (HMB) feature utilizes the DMA (Direct Memory Access) of PCI Express to allow SSDs to use some of the DRAM on PC system, instead of requiring the SSD to bring its own DRAM.

Secure Your Data

With support for TRIM, SMART and Over-Provision, GIGABYTE Gen4 4000E SSD ensures that your data is not only protected, but also optimized for stable and consistent performance over time.

SSD Tool Box

The newly updated SSD Tool Box is a software that gives users an overview of the SSD Status and various aspects such as model name, FW version, health condition and sensor temperature. Moreover, users can clear all the data with the Secure Erase function. You can download the SSD Tool Box from the link.

GIGABYTE CONTROL CENTER (GCC)

GIGABYTE CONTROL CENTER (GCC) is a unified software for all GIGABYTE supported products. It provides newly designed intuitive user interface to control all essential function.

- Unified software platform for all Gigabyte supported products
- Intuitive user interface for an eased experience
- Modularized control components only for installed hardware
- Auto update function to keep system up to date and support future products

Techninė specifikacija

Specifications	
Sandėlio grupė	Interne SSDs [+0][-0]
Features	
SSD capacity	500 GB
SSD form factor	M.2
Interface	PCI Express 4.0
NVMe	Yes
Memory type	3D NAND
Component for	PC
Hardware encryption	No

NVMe version	1.4
M.2 SSD size	2280 (22 x 80 mm)
Read speed	3600 MB/s
Write speed	3000 MB/s
PCI Express interface data lanes	x4
S.M.A.R.T. support	Yes
TRIM support	Yes
Mean time between failures (MTBF)	1500000 h
TBW rating	300
Power	
Power consumption (read)	4.3 W
Power consumption (write)	4.4 W
Power consumption (idle)	0.04 W
Weight & dimensions	
Width	22 mm
Depth	80 mm
Height	2.3 mm
Packaging data	
Package type	Box
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Matmenys ir svoris	
Svoris	0,03kg