

be quiet! TFX POWER 3 300W Gold power supply unit 20+4 pin ATX Black

Gamintojas: **BE QUIET!** · Modelis: **BN323** · EAN: **4260052188293** · Prekės kodas: **589517**



59,89 €

Kaina su PVM

Be PVM: **49,50 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 80 PLUS® Gold efficiency (up to 91.7%) for lower power consumption
- ✓ Strong dual 12V-rails for high stability and PCIe graphics card support
- ✓ 300W of continuous power
- ✓ High-quality temperature-controlled 80mm fan for low-noise operation of max. 21.7dB(A)
- ✓ Sleeved or flat black cables up to 60cm long
- ✓ Meets the latest safety and efficiency requirements
- ✓ Modern safety protections reliably defend against numerous failures
- ✓ Standby draw less than 0.17 watts
- ✓ Product conception, design and quality control in Germany



Aprašymas

TFX Power 3 300W Gold, the advanced, high-efficiency be quiet! compact PSU gives you more for your mini or media PC. It supports the latest standards while providing solid voltages and enough power to support a PCIe graphics card. The combination of quiet operation and reliability make the TFX Power 3 300W Gold the perfect choice for PCs with TFX form factor.

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzteile [+0][-0]
Power	
Total power	300 W
AC input voltage	100 - 240 V
Peak power	350 W
AC input frequency	50 - 60 Hz
Input current	4/2 A
Maximum input current (@110V)	4 A
Maximum input current (@220V)	2 A
Power factor	0.98
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	103 W
Combined power (+12V)	288 W
Combined power (+5V)	103 W
Max output current (+3.3V)	18 A
Max output current (+12V1)	13 A
Max output current (+12V2)	13 A
Max output current (+5V)	18 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A
Hold time	29 ms
Efficiency	90.6%
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage
Ports & interfaces	
Motherboard power connector	20+4 pin ATX
Peripheral (Molex) power connectors (4-pin)	2
Motherboard power cable length	35 cm
Number of SATA power connectors	3
SATA power cable length	300,450,600 mm
Peripheral (Molex) power cable length	300,450 mm
PCI Express power connectors (6+2 pin)	1
PCI Express power cable length	40 cm

CPU P4 connector (4-pin)	1
CPU power cable length	35 cm
Floppy drive power connector	1
Floppy disk drive cable length	60 cm
PCI Express connector	Yes
Cabling type	Non-Modular
Performance	
Purpose	PC
Power supply unit (PSU) form factor	TFX
80 PLUS certification	80 PLUS Gold
ATX version	2.52
EPS version	2.92
Noise level	21.7 dB
Mean time between failures (MTBF)	100000 h
Design	
Product colour	Black
Cooling type	Active
Fan diameter	8 cm
Number of fans	1 fan(s)
Illumination	No
Certificates	
Compliance certificates	RoHS, WEEE
Safety regulation & standards	
Safety	CE, CB, TÜV, CU
Weight & dimensions	
Width	85 mm
Depth	175 mm
Height	65 mm
Weight	1.1 kg
Packaging data	
Package width	159 mm
Package depth	80 mm
Package height	215 mm
Package weight	1.43 kg

Package type	Box
Technical details	
Sustainability certificates	ENERGY STAR, ErP
Sustainability compliance	Yes
Logistics data	
Shipping (inner) case length	47.4 cm
Shipping (inner) case width	27.5 cm
Shipping (inner) case height	19.5 cm
Products per shipping (inner) case	6 pc(s)
Shipping (inner) case gross weight	9.39 kg
Harmonized System (HS) code	84733020
Matmenys ir svoris	
Svoris	1,48kg