

Zebra DS3678-SR Handheld bar code reader 1D/2D LED Black, Green

Gamintojas: **ZEBRA** · Modelis: **DS3678-SR0F003VZWW** · EAN: **5711783323167** · Prekės kodas: **590279**



412,90 €

Kaina su PVM

Be PVM: **341,24 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Handheld bar code reader Black, Green
- ✓ Scanner type: 1D/2D Sensor type: LED
- ✓ Codabar, Code 11, Code 128, Code 39, Code 93, GS1-128 (UCC/EAN-128), MSI, Plessey, U.P.C. Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
- ✓ Tilt reading angle: -65 - 65°
- ✓ Wired & Wireless Standard interfaces: RS-232, USB, Keyboard wedge
- ✓ Bluetooth Low Energy (BLE)
- ✓ Power source type: Battery Lithium-Ion (Li-Ion) 3100 mAh

Aprašymas

UNSTOPPABLE PERFORMANCE FOR STANDARD RANGE 1D/2D BARCODE CAPTURE

As a member of the Zebra 3600 Ultra-Rugged Series of scanners, the practically indestructible 1D/2D DS3608-SR corded and DS3678-SR cordless scanners are ready for the world's toughest environments — the warehouse and manufacturing floor. Designed to capture virtually any barcode from near contact to as far as 5 ft./1.5 m away, these scanners are loaded with features that deliver truly unstoppable performance, redefining reliability and management simplicity. The result? The dependable, fast and accurate scanning you need to take the quality of your products and your customer service to the next level.

SUPERIOR PERFORMANCE

You get the ultimate in scanning performance — period. Your workers can scan virtually any 1D or 2D electronic or printed barcode in any condition, as fast as they can pull the trigger. With 30 percent more working range, it's easy to capture barcodes that are farther away. Even if barcodes are under shrinkwrap or damaged, dirty or poorly printed, no problem — this intelligent scanner can handle it all.

ULTRA-RUGGED DESIGN

The manufacturing plant floor is as tough as its gets — and the cost of unplanned downtime on the production line is astronomical. That’s why we created a new product category — the ultra-rugged scanner. The corded and cordless models are the only scanners in this class that are dust-tight, sprayproof and waterproofed to IP67, with an IP65-sealed cradle for a complete rugged cordless solution.

UNRIVALED MANAGEABILITY

With our complimentary industry-best tools, managing these scanners couldn’t be easier. You can remotely configure and upgrade your scanners, format data properly for instant transmission into your business applications, monitor battery statistics for your cordless models and more.

Techninė specifikacija

Specifications	
Sandėlio grupė	Scanner [+0][-0]
Scanning	
Type	Handheld bar code reader
Scanner type	1D/2D
Sensor type	LED
Linear (1D) barcodes supported	Codabar, Code 11, Code 128, Code 39, Code 93, GS1-128 (UCC/EAN-128), MSI, Plessey, U.P.C.
2D (matrix & stacked) barcodes supported	Aztec Code, Composite Codes, Data Matrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
Wavelength	610 nm
Tilt reading angle	-65 - 65°
Pitch reading angle	-65 - 65°
Yaw reading angle	-45 - 45°
Optical sensor resolution	1280 pixels
Ports & interfaces	
Connectivity technology	Wired & Wireless
Standard interfaces	RS-232, USB, Keyboard wedge
Wireless range	100 m
Bluetooth version	4
Bluetooth Low Energy (BLE)	Yes
Ethernet LAN	Yes
Performance	
Product colour	Black, Green
International Protection (IP) code	IP67
Protection features	Dust resistant, Shock resistant, Water resistant
LED indicators	Yes
Programming function	Yes

Power	
Power source type	Battery
Battery technology	Lithium-Ion (Li-Ion)
Battery capacity	3100 mAh
Number of reads per charge	100000
Weight & dimensions	
Weight	407 g
Width	142 mm
Depth	76 mm
Height	185 mm
Packaging data	
Cables included	USB
Charging base	No
Stand included	No
Operational conditions	
Operating temperature (T-T)	-20 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Technical details	
Compliance certificates	RoHS
Logistics data	
Harmonized System (HS) code	84716070
Matmenys ir svoris	
Svoris	0,52kg