

Barco ClickShare Hub Core video conferencing system Ethernet LAN Video conferencing service management system

Gamintojas: **BARCO** · Modelis: **R9861711EUB1** · EAN: **5415334054738** · Prekės kodas: **591482**



2 346,90 €

Kaina su PVM

Be PVM: **1 939,59 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wireless presentation: 4K content sharing with 1 Button
- ✓ Sustainable product with Barco Eco label A+
- ✓ Secure by design, cloud-managed, and built on the Microsoft Device Ecosystem platform (MDEP)
- ✓ Works as part of a room system bundle certified for Microsoft Teams
- ✓ Next-gen ClickShare Button with Wi-Fi 6E support and USB-C DisplayPort™



Aprašymas

ClickShare Hub Core is a modular, wireless video conferencing system designed for effortless hybrid meetings.

The Hub Core works with the ClickShare Control Panel* and enables participants to start their meeting with a simple tap. Sharing 4K content is just as easy thanks to the next-gen ClickShare Button.

For IT managers and integrators, ClickShare Hub Core offers a customizable solution for all room types, and both ad hoc and scheduled meetings. Built on the Microsoft Device Ecosystem Platform (MDEP), it guarantees enterprise-grade security and compliance.

Meeting room bundles for seamless hybrid collaboration

The ClickShare Hub Core and Sennheiser TeamConnect Bar S bundle is a certified Microsoft Teams Rooms solution designed for small meeting rooms. It combines secure 4K content sharing, high-quality audio and video, and cloud-managed performance – all in one easy-to-deploy package.

Certified for Microsoft Teams, ensuring seamless integration and a consistent user experience
Built on Microsoft Device Ecosystem Platform (MDEP) for secure, Android-based room system performance
One-click 4K content sharing with a next-gen ClickShare Button featuring Wi-Fi 6E and USB-C DisplayPort™

Next-gen ClickShare Button

The ClickShare Button 5th gen, featuring Wi-Fi 6E, offers faster speeds and more reliable connectivity for smooth, uninterrupted collaboration. Featuring USB-C DisplayPort™, it enables guest-friendly, plug-and-play sharing — no software or drivers needed. For added privacy and control, the ClickShare Button requires a deliberate press, preventing accidental sharing. Works seamlessly across all major OS in high-security environments
Built-in security and user control

Techninė specifikacija

Specifications	
Sandėlio grupė	Konferenzsysteme [+0][-0]
Performance	
Product type	Video conferencing service management system
Product colour	Black
Bluetooth	Yes
Bluetooth version	5.3
Noise level	25 dB
Video	
HD type	5K Ultra HD
Maximum video resolution	5120 x 2160 pixels
Supported graphics resolutions	1280 x 800 (WXGA), 5120 x 2160
Ports & interfaces	
HDMI output ports quantity	1
HDMI version	2
USB 2.0 Type-C ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	3
USB Type-C DisplayPort Alternate Mode	Yes
Ethernet LAN (RJ-45) ports	1
DisplayPort version	1.4
Buttons	
Presentation button included	Yes
Network	
Ethernet LAN	Yes

Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi	Yes
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax), Wi-Fi 7 (802.11be)
Networking standards	IEEE 802.15.1
Display	
Built-in display	No
Features	
Cable lock slot	Yes
Cable lock slot type	Kensington
Maximum operating distance	30 m
Logistics data	
Country of origin	China
Computer system	
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64
Mac operating systems supported	Mac OS X 14.0 Sonoma, Mac OS X 15.0 Sequoia
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 85%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	0 - 90%
Power	
Power source type	USB
Power consumption (max)	140 W
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	180 W
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Weight & dimensions	
Width	180 mm
Depth	180 mm
Height	37 mm

Weight	720 g
Receiver dimensions (WxDxH)	63 x 161.3 x 16 mm

Packaging content

External interface module included	Yes
Camera included	No
Control panel included	No
Packaging content	1 x ClickShare Button 5th Gen

Matmenys ir svoris

Svoris	1,33kg
--------	--------