

Samsung WE65FX interactive whiteboard 165.1 cm (65") 3840 x 2160 pixels Touchscreen Grey HDMI

Gamintojas: **SAMSUNG** · Modelis: **LH65WEFWLGCXEN** · EAN: **8806097652939** · Prekės kodas: **592269**

1 241,90 €

Kaina su PVM

Be PVM: **1 026,36 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ OS-Free with Plug and Play
- ✓ Up to 40 simultaneous touchpoints
- ✓ Dedicated annotation button

Aprašymas

Samsung WE65FX. Bildschirmdiagonale: 165,1 cm (65"), Helligkeit: 350 cd/m², Display-Auflösung: 3840 x 2160 Pixel. Benutzerspeicher: 32 GB. Schnittstelle: HDMI, USB-Stecker: USB Typ-A, USB Typ-C. Produktfarbe: Grau, Panel-Montage-Schnittstelle: 600 x 400 mm, Zertifizierung: IEC 62368-1 Edition 3&IEC 60950-1 UL62368-1 edition 3 GB4943.1-2022 PSB+ IEC 62368-1 NOM-019 K.... Betriebszeiten (Stunden/Tage): 12/7

Techninė specifikacija

Display	
Display diagonal	165.1 cm (65")
Touchscreen	Yes
Display brightness	350 cd/m²
Display resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Panel type	ADS
Contrast ratio (typical)	1200:1

Response time	8 ms
Maximum refresh rate	60 Hz
Pixel frequency (max)	78 MHz
Touch technology	Multi-touch
Touchscreen type	Infrared
Number of simultaneous touchpoints	40
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.372 x 0.372 mm
Colour gamut	72%
Maximum pixel clock	78 MHz
Haze rate	25%
Technology	Infrared (IR)
Computer system	
User memory	32 GB
Ports & interfaces	
Interface	HDMI
HDCP	Yes
HDCP version	2.2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
USB 2.0 ports quantity	1
USB connector type	USB Type-A, USB Type-C
HDMI ports quantity	3
USB Type-C ports quantity	2
HDMI version	2
Line-in	Yes
Line-out	Yes
OPS slot	1
RS-232 ports	1
Ergonomics	
Product colour	Grey
VESA mounting	Yes
Panel mounting interface	600 x 400 mm

Certification	IEC 62368-1 Edtion 3&IEC 60950-1 UL62368-1 edition 3 GB4943.1-2022 PSB+ IEC 62368-1 NOM-019 K 62368 IRAM+ IEC 62368-1 EAC+ IEC 62368-1 INMETRO+ IEC 62368-1 SASO+ IEC 62368-1 BSMI+ IEC 62368-1 IEC 62368-1/AS/NZS 62368-1 IEC60950-1 / IS13252
Performance	
Operating hours (hours/days)	12/7
Power	
Power consumption (typical)	350 W
Power consumption (standby)	0.5 W
Power consumption (sleep)	0.5 W
AC input voltage	100-240 V
AC input frequency	50/60 Hz
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Weight & dimensions	
Width	1491 mm
Height	898 mm
Depth	99 mm
Weight	30.5 kg
Packaging data	
Package width	1628 mm
Package depth	185 mm
Package height	1014 mm
Package weight	38 kg
Sustainability	
Compliance certificates	VCCI
Matmenys ir svoris	
Svoris	4,10kg