

StarTech.com 1-Port Parallel PCIe Card - PCI Express to Parallel DB25 Adapter Card - Desktop Expansion LPT Controller for Printers, Scanners & Plotters - SPP/ECP - Standard/Low Profile

Gamintojas: **STARTECH** · Modelis: **PEX1P2** · EAN: **065030891400** · Prekės kodas: **593085**

35,90 €

Kaina su PVM

Be PVM: **29,67 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **1-PORT PARALLEL PCIe CARD:** Using a 1x PCI Express 2.0 Gen 1 slot, add a DB25 parallel communications port to your computer; Installs in full/standard or low profile PCIe cards slots (brackets incl.); Latest version of our popular parallel card PEX1P
- ✓ **TECH SPECS:** Parallel port LPT controller card supports SPP/Byte/Nibble/ECP modes / Compatible with IEEE 1284 / Speeds up to 2.5Mbps / Asix AX99100 chip / Full profile bracket pre-installed
- ✓ **VERSATILE APPLICATIONS:** Parallel port expansion card works with printers, scanners, plotters, point of sale terminals, PLCs, control/automation in factories, scientific sensors, medical equipment, oscilloscope
- ✓ **WIDE COMPATABILITY:** Fully compliant with PCI Express Base Specifications Revision 1.1 and PCI Power Mgmt 1.2; Compatible with PCI-e x1 slot and up; Supports Windows (incl. XP and up) Windows Server (2003 and up) and Linux (2.6.X and up)
- ✓ **STARTECH.COM ADVANTAGE:** IT professionals' choice for over 30 years; These PCIe Parallel adapter card is backed for 2-years by StarTech.com, incl. free 24/5 North America based multi-lingual tech support

Aprašymas

PCI Express 2.0 | LPT | PCIe 1x Slot | 2.5 Mbps | 2-Year Warranty

This PCIe Parallel controller card installs into an available PCI-Express x1 slot in your computer and enables you to add DB25 parallel communication port to your system.

Adds a Parallel Port to Your Desktop Computer

The controller card features an Asix AX99100 chip and enables you to connect a DB25 device to your desktop computer. The parallel port port is ideal for connecting printers, scanners, plotters, point-of-sale terminals, PLCs, scientific sensors, medical equipment or oscilloscopes. The card can also be used in factories, to control or automate equipment. The parallel (LPT) port supports SPP/Byte/Nibble/ECP modes and is compatible with PCI Power Management 1.2 and IEEE 1284 for speeds up to 2.5Mbps.

Wide Installation Compatibility

This add-on card includes both full-profile and low-profile installation brackets (full-profile bracket pre-installed) ensuring you can install it into either a full or low-profile PCIe 2.0 x1 slot (backward compatible with PCIe 1.1). For wide platform support the card is compatible with Windows (XP or higher), Windows Server (2003 or higher), and Linux (2.6.X or higher).

PEX1P2 is backed by a StarTech.com 2-year warranty with free 24/5 multi-lingual North American based technical support. StarTech.com has been the IT professionals' choice for over 30 years.

Techninė specifikacija

Ports & interfaces	
Host interface	PCIe
Output interface	Parallel
Expansion card standard	PCIe 1.0a
Parallel ports quantity	1
Design	
Internal	Yes
Product colour	Black, Steel
Mean time between failures (MTBF)	26297 h
Features	
Chipset	PLX/Oxford - OXPCle952
System requirements	
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Linux operating systems supported	Yes
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Technical details	
Compliance certificates	CE, RoHS

Weight & dimensions

Width	110 mm
Depth	210 mm
Height	120 mm
Weight	42 g

Packaging data

Mounting brackets included	Yes
Drivers included	Yes
Manual	Yes
Package width	216 mm
Package depth	146 mm
Package height	37 mm
Package weight	133 g

Logistics data

Harmonized System (HS) code	84733020
Products per master (outer) case	40 pc(s)
Master (outer) case width	450 mm
Master (outer) case length	379 mm
Master (outer) case height	327 mm

Other features

Data transfer rate	2.5 Mbit/s
Material	Steel