

Equip 58/80mm Thermal POS Receipt Printer with Auto Cutter, USB/Bluetooth/WiFi/Cash Drawer connection

Gamintojas: **EQUIP** · Modelis: **351006** · EAN: **4015867242568** · Prekės kodas: **594405**



140,90 €

Kaina su PVM

Be PVM: **116,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wide compatibility with most types of business software
- ✓ High-speed, stable with low-noise printing
- ✓ Easy paper loading system
- ✓ Compatible with POS/ESC command set
- ✓ Thermal printing, no need for ink ribbon and toner
- ✓ Work with standard 50/80mm thermal paper



Aprašymas

The equip® POS range offers reliable equipment to suit a wide variety of Point of Sale (POS) situations and business needs. The solutions are designed for retail, service-type businesses or the food and beverage industry.

The equip® Thermal POS Receipt Printers are perfect for situations such as customer checkout and food and beverage operations. The printer is compatible with ESC/POS printing commands and offers high-speed, stable printing and auto-cutter functionality.

Techninė specifikacija

Specifications

Sandėlio grupė	Drucker [+0][-0]
Printing	
Print technology	Thermal
Type	POS printer
Maximum resolution	203 x 203 DPI
Print columns	576 dots/line
Print speed	300 mm/sec
Paper handling	
Supported paper width	50 - 80 mm
Maximum printing width	7.2 cm
Ports & interfaces	
Connectivity technology	Wired & Wireless
USB port	Yes
Serial interface	No
USB 2.0 ports quantity	1
USB connector	USB Type-B
Bluetooth	Yes
Standard interfaces	RJ-11
Network	
Ethernet LAN	No
Wi-Fi	Yes
Features	
Built-in barcodes	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, EAN13, EAN8, ITF, QR Code, UPC-A, UPC-E
Page description languages	ESC/POS
Cutter	Yes
Magnetic stripe reader	No
Print head life	100 km
Country of origin	China
Design	
Product colour	Black
Built-in display	No
Power	
Power source type	DC

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
DC output voltage	24 V
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	20 - 80%
System requirements	
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64
Mac compatibility	Yes
Mac operating systems supported	Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma, Mac OS X 15.0 Sequoia
Mobile operating systems supported	Android
Linux operating systems supported	Ubuntu 12.04, Ubuntu 14.04
Weight & dimensions	
Width	195 mm
Depth	145 mm
Height	143.3 mm
Weight	1.2 kg
Packaging data	
Cables included	AC, USB
Package width	201 mm
Package depth	230 mm
Package height	152 mm
Package weight	1.6 kg
Packaging content	
Drivers included	Yes
Quick start guide	Yes
AC adapter included	Yes

Logistics data	
Products per master (outer) case	8 pc(s)
Master (outer) case width	425 mm
Master (outer) case length	477 mm
Master (outer) case height	328 mm
Master (outer) case gross weight	13 kg
Customs product code (TARIC)	8443321000
Technical details	
Compliance certificates	CE, RoHS