



## CHARGER WALL 30W/73424 LINDY



Modelis: 73424

Gamintojas: LINDY

EAN: 4002888734240

Prekės kodas: 59681

---

# 17.99€

---

The Lindy 30W USB Type A & C PD Charger can charge two devices simultaneously. 30W Power Delivery are supported by the USB Type C port while the USB Type A port provides fast charging with up to 18W. When both ports are used in parallel a maximum power of 15W will be provided.

Featuring both a USB Type C female and a USB Type A female port this charger is ideal for use with most popular smartphones and iOS devices. Supporting power delivery of 30W, connected devices can be provided with faster charging than what is possible from a standard Type C or A charger supplied with many devices.

For safe charging the device includes overcharge, overcurrent, overtemperature and short circuit protection. As this charger is rated at Level 6 for efficiency, it also meets the highest current level of energy efficiency standards.

- Charges and powers two devices simultaneously via a USB Type C and a USB Type A port
- 30W Power Delivery via the USB Type C port provides fast charging for smartphones, tablets, laptops and other mobile devices
- Compact design for maximum mobility
- Built-in safety features such as overvoltage and overcurrent protection

Summary: Lindy 73424. Charger type: Indoor, Power source type: AC, Charger compatibility: Universal. Input voltage: 100 - 240 V, Maximum output voltage: 20 V. USB 2.0 ports quantity: 1, USB Type-C ports quantity: 1, Fast charging, Power protection features: Over current, Over voltage, Overheating, Short circuit. Product colour: White | Vendor Homepage: <https://www.lindy-international.com/30W-USB-Type-A-C-Charger.htm?websale8=ld0101.ld021102&pi=73424&ci=5012> | Charger compatibility: Universal | Charger type: Indoor | Fast charging: Yes | Fast charging technology: Power Delivery 3.0 | Number of simultaneously connected devices (max): 2 | Power protection features: Over current/Over voltage/Overheating/Short circuit | Power source type: AC | USB 2.0 ports quantity: 1 | USB Power Delivery (USB PD): Yes | USB Power Delivery revision: 3.0 | USB Power Delivery up to: 30 | USB Type-C ports quantity: 1 | Connector material: Copper | Housing material: Polyvinyl chloride (PVC) | Product colour: White | Average active efficiency: 81.38% | Efficiency at low load (10%): Yes | Input current: 0.6 | Input frequency: 50/60 | Input voltage: 100 - 240 | Maximum output voltage: 20 | Maximum power: 30 | Minimum output voltage: 5 | Output current (12V): 2.5 | Output current (15V): 2 | Output current (20V): 1.5 | Output current (5V): 3 | Output current (9V): 3 | Output voltage accuracy ( $\pm$ ): 5 | Power consumption (no load): 0.1 | Depth: 85.3 | Height: 41.6 | Weight: 40 | Width: 26.8 | Package depth: 100 | Package height: 45 | Package type: Box | Package weight: 60 | Package width: 80 | Operating relative humidity (H-H): 20 - 90 | Operating temperature (T-T): 0 - 25 | Storage relative humidity (H-H): 20 - 90 | Storage temperature (T-T): -20 - 70 | Manual: Yes | Quantity per pack: 1 | Compliance certificates: CE/REACH/RoHS | Sustainability certificates: ErP | Sustainability compliance: Yes | Units per Shipping Box: 1 | Unit Calculated Volume: 0.000348 | Unit Calculated Weight: 0.083