



Hikvision DS-2CD1161G2-LIU IP camera



Modelis: DS-2CD1161G2-LIU

Gamintojas: HIKVISION

EAN: 6936422131012

Prekės kodas: 597631

84.99€

Power over Ethernet (PoE): Yes | Minimum illumination: 0 lx | Ethernet LAN (RJ-45) ports: 1 | Package weight: 800 g | Compatible memory cards: MicroSDXC | Compatible memory cards: MicroSDHC | Built-in microphone: Yes | Highlight Compensation (HLC): Yes | Storage temperature (T-T): -30 - 60 °C | Tilt angle range: 0 - 75° | Housing material: Plastic | Depth: 97.6 mm | Housing material: Metal | Ethernet LAN data rates: 10,100 Mbit/s | Package height: 141 mm | Form factor: Dome | Maximum resolution: 3200 x 1800 pixels | Connectivity technology: Wired | Bit rate: 32 Kbps - 16 Mbps | Operating temperature (T-T): -30 - 60 °C | Package width: 150 mm | Compatible memory cards: MicroSD (TransFlash) | Operating relative humidity (H-H): 0 - 95% | Product colour: White | Quality of Service (QoS) support: Yes | Package depth: 150 mm | Ethernet LAN: Yes | Night vision distance: 30 m | Storage relative humidity (H-H): 0 - 95% | LED type: IR/White | Number of cameras: 1 | International Protection (IP) code: IP67 | Wide Dynamic Range (WDR): 120 dB | Weight: 550 g | Web-based management: Yes | Type: IP security camera | Number of users: 32 user(s) | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Sensor type: CMOS | Camera shutter speed: 1/3 - 1/100000 s | Angle of rotation: 355° | Video motion detection: Yes | Total megapixels: 6 MP | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Infra-red wavelength: 850 nm | Password protection: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Recognize distance (wide): 23 m | Progressive scan: Yes | Night vision: Yes | Maximum frame rate: 20 fps | Pan range: 0 - 355° | Video compression formats: H.265+ | Region of Interest (ROI) encoding: Yes | Video compression formats: H.265 | Day/night mode: Yes | Noise filter: Yes | Video compression formats: H.264+ | Maximum memory card size: 512 GB | Mirror: Yes | Heartbeat: Yes | Detect distance (wide): 115 m | Maximum aperture number: 1.6 | Video compression formats: M-JPEG | Observe distance (wide): 45 m | Diameter: 12.1 cm | Signal-to-Noise Ratio (SNR): 52 dB | Sample rate: 8 kHz / 16 kHz | Power management: DC 12 V | Video compression formats: H.264 | DC output current: 0.5 A | Identify distance (wide): 11 m | Sustainability certificates: WEEE | Sustainability certificates: REACH | Lens viewing angle, vertical: 55 - 38° | PoE standard: IEEE 802.3af | Lens viewing angle, diagonal: 127 - 96° | Lens viewing angle, horizontal: 105 - 78° | Mono sound: Yes