Hikvision DS-2CD1161G2-LIU IP camera

Gamintojas: **HIKVISION** · Modelis: **DS-2CD1161G2-LIU** · EAN: **6936422131012** · Prekės kodas: **597631**







86,90 €

Kaina su PVM

Be PVM: **71,82 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Aprašymas

Ethernet LAN data rates: 10,100 Mbit/s | International Protection (IP) code: IP67 | Package weight: 800 g | Compatible memory cards: MicroSDXC | Operating relative humidity (H-H): 0 - 95% | Type: IP security camera | Housing material: Metal | Highlight Compensation (HLC): Yes | Storage relative humidity (H-H): 0 - 95% | Ethernet LAN (RJ-45) ports: 1 | Number of cameras: 1 | Web-based management: Yes | Bit rate: 32 Kbps - 16 Mbps | Compatible memory cards: MicroSD (TransFlash) | Minimum illumination: 0 lx | Package width: 150 mm | Night vision distance: 30 m | Form factor: Dome | Operating temperature (T-T): -30 - 60 °C | Product colour: White | Quality of Service (QoS) support: Yes | Package depth: 150 mm | Weight: 550 g | LED type: IR/White | Storage temperature (T-T): -30 - 60 °C | Built-in microphone: Yes | Maximum resolution: 3200 x 1800 pixels | Wide Dynamic Range (WDR): 120 dB | Housing material: Plastic | Compatible memory cards: MicroSDHC | Package height: 141 mm | Depth: 97.6 mm | Tilt angle range: 0 - 75° | Ethernet LAN: Yes | Connectivity technology: Wired | Power over Ethernet (PoE): Yes | DC output current: 0.5 A | Mirror: Yes | Night vision: Yes | Power management: DC 12 V | Heartbeat: Yes | Sample rate: 8 kHz / 16 kHz | Diameter: 12.1 cm | Sensor type: CMOS | Angle of rotation: 355° | Signal-to-Noise Ratio (SNR): 52 dB | Password protection: Yes | Maximum memory card size: 512 GB | Number of users: 32 user(s) | Infra-red wavelength: 850 nm | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Region of Interest (ROI) encoding: Yes | Total megapixels: 6 MP | Progressive scan: Yes | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Recognize distance (wide): 23 m | Video motion detection: Yes | Identify distance (wide): 11 m | Observe distance (wide): 45 m | Video compression formats: H.265 | Noise filter: Yes | Pan range: 0 - 355° | Camera shutter speed: 1/3 - 1/100000 s | Maximum frame rate: 20 fps | Day/night mode: Yes | Video compression formats: M-JPEG | Video compression formats: H.264 | Video compression formats: H.265+ | Video compression formats: H.264+ | Detect distance (wide): 115 m | Maximum aperture number: 1.6 | Lens viewing angle, diagonal: 127 - 96° | Lens viewing angle, horizontal: 105 - 78° | Sustainability certificates: WEEE | Lens viewing angle, vertical: 55 - 38° | Sustainability certificates: REACH | Mono sound: Yes | PoE standard: IEEE 802.3af

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	15,00cm × 15,00cm × 14,00cm
Svoris	0,66kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903