



Hikvision DS-2CD2343G2P-LISU/SL 180 IP camera

Modelis: DS-2CD2343G2P-LISU/SL 180°

Gamintojas: HIKVISION

EAN: 6936422195809

Prekės kodas: 597632

175.99€

Operating relative humidity (H-H): 0 - 95% | International Protection (IP) code: IP67 | LED type: IR | Weight: 808 g | Number of cameras: 1 | Ethernet LAN data rates: 10,100 Mbit/s | Package height: 160 mm | Storage relative humidity (H-H): 0 - 95% | Quality of Service (QoS) support: Yes | Package width: 170 mm | Form factor: Dome | Bit rate: 32 Kbps - 16 Mbps | Maximum resolution: 3000 x 1328 pixels | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): -30 - 60 °C | Minimum illumination: 0 lx | Connectivity technology: Wired | Power over Ethernet (PoE): Yes | Depth: 125 mm | Ethernet LAN: Yes | Tilt angle range: 0 - 75° | Type: IP security camera | Product colour: White | Storage temperature (T-T): -30 - 60 °C | Package depth: 170 mm | Compatible memory cards: MicroSDXC | Package weight: 1.05 kg | Night vision distance: 30 m | Wide Dynamic Range (WDR): 120 dB | Housing material: Metal | Built-in microphone: Yes | Compatible memory cards: MicroSD (TransFlash) | Compatible memory cards: MicroSDHC | Identify distance (wide): 4 m | Diameter: 13.9 cm | Night vision: Yes | Signal-to-Noise Ratio (SNR): 52 dB | Optical sensor size: 25.4 / 2.5 mm (1 / 2.5") | Sensor type: CMOS | Progressive scan: Yes | Highlight Compensation (HLC): Yes | Maximum memory card size: 512 GB | Angle of rotation: 360° | Camera shutter speed: 1 - 1/100000 s | Total

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

megapixels: 4 MP | Video compression formats: H.265+ | Region of Interest (ROI) encoding: Yes | Day/night mode: Yes | Video motion detection: Yes | Recognize distance (wide): 8 m | Observe distance (wide): 16 m | Video compression formats: H.264+ | Pan range: 0 - 360° | Maximum aperture number: 1.6 | Video compression formats: M-JPEG | Number of users: 32 user(s) | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | DC output current: 0.83 A | Video compression formats: H.265 | Video compression formats: H.264 | Detect distance (wide): 42 m | Power management: DC 12 V | Maximum frame rate: 20 fps | Mono sound: Yes | Password protection: Yes | PoE standard: IEEE 802.3af | Lens viewing angle, horizontal: 180° | Sustainability certificates: REACH | Sustainability certificates: WEEE | Infra-red wavelength: 850 nm | Lens viewing angle, vertical: 77° | Sample rate: 8 kHz / 16 kHz | Heartbeat: Yes