



TP-Link TL-MR100 wireless router Fast Ethernet Single-band (2.4 GHz) 4G Black

Modelis: TL-MR100

Gamintojas: TP-LINK

EAN: 1210002609258

Prekės kodas: 597692

59.99€

Receiver sensitivity: 11g 54M: -74dBm 11n HT20: -71dBm 11n HT40: -67dBm | Certification: CE, RoHS | Supported network protocols: IPv4, IPv6 | Output current: 0.85 A | DHCP server: Yes | Quick installation guide: Yes | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | 4G bands supported: 2600 | 4G bands supported: 2500 MHz | Linux operating systems supported: Yes | Wi-Fi standards: 802.11b | Height: 36 mm | 4G bands supported: 900 | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Firewall: Yes | Ethernet LAN interface type: Fast Ethernet | WLAN data transfer rate (max): 300 Mbit/s | 4G bands supported: 2300 | Product type: Tabletop router | IP address filtering: Yes | Universal Plug and Play (UPnP): Yes | 4G bands supported: 1800 | 3G standards: HSPA | Package height: 66 mm | Wi-Fi Multimedia (WMM)/(WME): Yes | Depth: 114 mm | 4G bands supported: 1900 | Antennas quantity: 2 | On/off switch: Yes | Ethernet LAN: Yes | USB port: No | Memory card slot(s): No | 4G bands supported: 2100

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| 4G bands supported: 800 | 4G standard: LTE-TDD & LTE-FDD | Wi-Fi standards: 802.11g | Cabling technology: 10/100Base-T(X) | WAN connection type: RJ-45 | Harmonized System (HS) code: 85176990 | Ethernet WAN: Yes | Wi-Fi band: Single-band (2.4 GHz) | Width: 154 mm | SIM card slot: Yes | Output voltage: 9 V | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | 3G standards: UMTS | WPS push button: Yes | DMZ support: Yes | Port triggering: Yes | SIM card type: MicroSIM | Guest access: Yes | 3G/4G USB modem compatibility: No | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n): 20 dBmW | 3G bands supported: 850 | 3G bands supported: 900 | 3G bands supported: 2100 | Mobile network generation: 4G | Mac operating systems supported: Yes | Security algorithms: 128-bit WEP | Security algorithms: WPA | Security algorithms: WPA2-PSK | Operating relative humidity (H-H): 10 - 90% | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Stateful Packet Inspection (SPI): Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 | Antenna connector type: N-type | Power source type: DC | Ethernet LAN (RJ-45) ports: 2 | DHCP client: Yes | Wireless radio: Yes | MAC address filtering: Yes | 4G: Yes | Networking standards: IEEE 802.11b | Weight: 150 g | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | 3G: Yes | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows XP | Wireless statistics: Yes | Cables included: LAN (RJ-45) | Package width: 293 mm | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows 2000 | Product colour: Black | Windows operating systems supported: Windows 8 | Reset button: Yes | Windows operating systems supported: Windows NT | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 161 mm | Windows operating systems supported: Windows 7 | AC adapter included: Yes | DC-in jack: Yes | Package weight: 480 g | Operating temperature (T-T): 0 - 40 °C | Antenna design: External | Schedule access: Yes