



TP-Link 5-Port Gigabit Easy Smart PoE Switch with 4- Port PoE+



Modelis: TL-SG105PE

Gamintojas: TP-LINK

EAN: 1210002616850

Prekės kodas: 597694

44.99€

Certification: FCC, CE, RoHS | Virtual LAN features: Tagged VLAN | Virtual LAN features: Port-based VLAN | Depth: 98 mm | Height: 25 mm | Gigabit Ethernet (copper) ports quantity: 5 | Broadcast storm control: Yes | Store-and-forward: Yes | Width: 99.8 mm | Rack mounting: No | Switch type: Managed | Copper ethernet cabling technology: 100BASE-TX | Packet buffer memory: 1 MB | Link aggregation: Yes | Number of queues: 4 | Switch layer: L2 | Forwarding rate: 7.44 Mpps | Jumbo frames support: Yes | Jumbo frames: 16000 | VLAN support: Yes | Loop protection: Yes | Heat dissipation: 256.3 BTU/h | Harmonized System (HS) code: 85176990 | Switching capacity: 10 Gbit/s | Power source: DC | IGMP snooping: Yes | Package height: 121 mm | Rate limiting: Yes | Cable types supported: Cat3 | Copper ethernet cabling technology: 1000BASE-T | Power supply included: Yes | MAC address table: 2000 entries | Port mirroring: Yes | Auto MDI/MDI-X: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

technology: 100BASE-FX | Cable types supported: Cat6 | Auto-negotiation: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | Basic switching RJ-45 Ethernet ports quantity: 5 | Total Power over Ethernet (PoE) budget: 65 W | Power over Ethernet plus (PoE+) ports quantity: 4 | User guide: Yes | Flow control support: Yes | Number of VLANs: 4000 | 10G support: No | Fanless: Yes | Input voltage: 53.5 V | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | LED indicators: Activity | LED indicators: Status | Operating temperature (T-T): 0 - 40 °C | LED indicators: Speed | LED indicators: Link | LED indicators: PoE | Package depth: 196 mm | Input current: 1.31 A | Product colour: Black | Power consumption (max): 75.16 W | LED indicators: Power | Package width: 131 mm | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Web-based management: Yes | Networking standards: IEEE 802.3af | Storage relative humidity (H-H): 5 - 95% | Package weight: 770 g | Operating relative humidity (H-H): 10 - 90%