



TP-Link Omada 24-Port Gigabit L2+ Managed Switch with 4 SFP Slots



Modelis: SG3428

Gamintojas: TP-LINK

EAN: 1210002611886

Prekės kodas: 597695

211.99€

Web-based management: Yes | MAC address filtering: Yes | Operating relative humidity (H-H): 10 - 90% | Storage relative humidity (H-H): 5 - 90% | Depth: 180 mm | Cables included: LAN (RJ-45) | Networking standards: IEEE 802.3u | Switching capacity: 56 Gbit/s | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE): No | Width: 440 mm | Power consumption (max): 20.6 W | Power supply included: No | Networking standards: IEEE 802.3ab | Product colour: Black | VLAN support: Yes | Rack mounting: Yes | Quick start guide: Yes | Number of fans: 0 fan(s) | Power source: AC | Networking standards: IEEE 802.3i | Ethernet LAN data rates: 10,100,1000 Mbit/s | Networking standards: IEEE 802.3z | Height: 44 mm | Jumbo frames support: Yes | Operating temperature (T-T): 0 - 45 °C | IGMP snooping: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Multicast support: Yes | Form factor: 1U | AC input frequency: 50/60 Hz | Packet buffer memory: 12 MB | Number of VLANs: 4000 | MAC address table: 16000 entries | SFP module slots quantity: 4 | DHCP features: DHCPv6 client | AC input voltage: 100 - 240 V | DHCP features:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

DHCP client | DHCP features: DHCP relay | 10G support: No | DHCP features: DHCPv6 snooping | DHCP features: DHCP snooping | LED indicators: Yes | DHCP features: DHCP server | Switch type: Managed | Heat dissipation: 70.3 BTU/h | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 24 | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Store-and-forward: Yes | Management protocols: SNMPv1/v2c/v3, SNTTP | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Static port security: Yes | Port mirroring: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Configuring Location Settings (CLI): Yes | Flow control support: Yes | MIB support: Yes | SSH/SSL support: Yes | Console port: RJ-45/micro-USB | Cloud-managed: Yes | ARP inspection: Yes | Virtual LAN features: Protocol-based VLAN | Rate limiting: Yes | GARP VLAN Registration Protocol (GVRP): Yes | IPv4 & IPv6 features: IPv6 tracer | Policy-based routing: Yes | Authentication: MAC-based authentication, Port-based authentication | Virtual LAN features: Tagged VLAN | Virtual LAN features: Private VLAN | Number of static routes: 48 | IPv4 & IPv6 features: IPv6 Telnet | Head-of-line (HOL) blocking: Yes | Forwarding rate: 41.66 Mpps | IP-MAC-Port binding: Yes | IPv4 & IPv6 features: IPv6 ping | Virtual LAN features: Voice VLAN | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | Loop protection: Yes | Access Control List (ACL): Yes | IP routing: Yes | Switch layer: L2/L3 | System event log: Yes | BPDU filtering/protection: Yes | Static route: Yes | Authentication type: AAA, RADIUS, TACACS+ | IPv6 routes: 48 | IPv4 routes: 48