



**Mainboard
ASROCK Intel
H810 LGA 1851
(Socket V1)
micro ATX RAM
DDR5-SDRAM
2xSlots
1xNumber of
M.2 (M) slots
H810M-PGEN5**

Modelis: H810M-P GEN5

Gamintojas: ASROCK

EAN: 4711581494206

Prekės kodas: 597769

86.99€

Hyper M.2 Gen4 x4

Supports PCI Express 4.0 M.2 SSDs, it is capable of perform twice the speed compared to previous 3rd generation, giving a lightning fast data transferring experience.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Aluminum Heatsink

The first thing that catches the eye is the optimized Aluminum Heatsink Design. Heatsinks are crucial for efficient heat dissipation, especially during heavy workloads like gaming or productivity tasks. Motherboard that built with heatsinks can effectively manage thermal performance, hence ensure system stability and durability effortlessly.

POLYCHROME RGB

This motherboard features onboard RGB headers and addressable RGB headers that allow motherboard to be connected to compatible LED devices such as strip, CPU fans, coolers, chassis and so on. Users may also synchronize RGB LED devices across the Polychrome RGB Sync-certified accessories to create their own unique lighting effects.

SignalRGB

SignalRGB unifies your RGB devices, offering seamless customization, game-reactive effects, macro automation, and system monitoring. The official partnership empowers ASRock motherboards with advanced lighting control, enhances compatibility with a diverse range of RGB devices, and provides greater customization flexibility.

M.2 (KEY E) For WiFi

Besides the onboard LAN port, users may also choose wireless connections by M.2 (Key E) slot.

Dual Graphics Outputs

Complete with two types of most used connectors! Packed with a HDMI + DisplayPort combo, you have more graphics output options now.

Summary: Asrock H810M-P Gen5. Processor manufacturer: Intel, Processor socket: LGA 1851 (Socket V1), Compatible processor series: Intel Core Ultra (Series 2). Supported memory types: DDR5-SDRAM, Maximum internal memory: 128 GB, Memory slots type: DIMM. Supported storage drive interfaces: SATA III, M.2, Supported storage drive types: HDD & SSD. LAN controller: Realtek RTL8111H. Component for: PC, Motherboard form factor: micro ATX, Motherboard chipset family: Intel | Vendor Homepage: <https://www.asrock.com/MB/Intel/H810M-P%20Gen5/index.asp#Overview> | Audio chip: Realtek ALC897 | Audio output channels: 7.1 | Component for: PC | Motherboard chipset: Intel H810 | Motherboard chipset family: Intel | Motherboard form factor: micro ATX | Windows operating systems supported: Windows 11 x64 | Compatible processor series: Intel Core Ultra (Series

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

2) | Maximum number of SMP processors: 1 | Processor manufacturer: Intel | Processor socket: LGA 1851 (Socket V1) | ECC compatibility: Non-ECC | Maximum internal memory: 128 | Memory channels: Dual-channel | Memory slots type: DIMM | Number of memory slots: 2 | Supported memory types: DDR5-SDRAM | Unbuffered memory: Yes | Supported storage drive interfaces: SATA III,M.2 | Supported storage drive types: HDD & SSD | HDCP: Yes | HDCP version: 2.3 | ATX Power connector (24-pin): Yes | CPU fan connector: Yes | EPS power connector (8-pin): Yes | Front panel audio connector: Yes | Number of chassis fan connectors: 1 | Number of CPU fan connectors: 1 | Number of EPS power connectors (8-pin): 1 | Number of RGB LED pin headers: 2 | Number of SATA III connectors: 4 | RGB LED pin header: Yes | TPM connector: Yes | USB 2.0 connectors: 1 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | DisplayPort version: 1.4 | DisplayPorts quantity: 1 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | Line-in: Yes | Microphone in: Yes | USB 2.0 ports quantity: 4 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | Ethernet LAN: Yes | LAN controller: Realtek RTL8111H | Wi-Fi: No | Number of M.2 (M) slots: 1 | PCI Express x1 (Gen 4.x) slots: 1 | PCI Express x16 (Gen 5.x) slots: 1 | BIOS memory size: 256 | BIOS type: EFI AMI | Depth: 193 | Width: 244 | Cables included: SATA | Screws included: Yes | Product Net Weight: 0.9 | Shipping Box Height: 28.5 | Unit Calculated Volume: 0.004893 | Unit Calculated Weight: 0.99 | Units per Pallet: 0 | Units per Shipping Box: 10