



Mainboard ASROCK AMD A620A Socket AM5 micro ATX RAM DDR5- SDRAM 2xSlots 1xNumber of M.2 (M) slots A620AM-P

Modelis: A620AM-P

Gamintojas: ASROCK

EAN: 4711581495111

Prekės kodas: 597770

83.99€

Dr. MOS

Dr.MOS is an integrated power stage optimized for synchronous buck-set down voltage applications, delivering higher current and better thermal efficiency than traditional MOSFETs, ensuring enhanced stability.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

2oz Copper PCB

2 ounce copper inner layers that provide stable signal traces and power shapes! Delivering lower temperature and higher energy efficiency for overclocking.

Hyper M.2 Gen4 x4

Supports PCI Express 4.0 M.2 SSDs, it is capable of perform twice the speed compared to previous 3rd generation, giving a lightning fast data transferring experience.

Front USB 3.2 Gen1 Type-C

Front USB 3.2 Gen1 Type-C header delivers up to 5 Gbps data transfer rate and next generation reversible USB design to the front panel of computer case.

POLYCHROME RGB

This motherboard features onboard RGB headers and addressable RGB headers that allow motherboard to be connected to compatible LED devices such as strip, CPU fans, coolers, chassis and so on. Users may also synchronize RGB LED devices across the Polychrome RGB Sync-certified accessories to create their own unique lighting effects.

SignalRGB

SignalRGB unifies your RGB devices, offering seamless customization, game-reactive effects, macro automation, and system monitoring. The official partnership empowers ASRock motherboards with advanced lighting control, enhances compatibility with a diverse range of RGB devices, and provides greater customization flexibility.

M.2 (KEY E) For WiFi

Besides the onboard LAN port, users may also choose wireless connections by M.2 (Key E) slot.

Post Status Checker

Displays the real-time status of CPU, DRAM, VGA, and BOOT device with colored LEDs during startup. A simple and efficient way to check system operation at a glance.

Summary: Asrock A620AM-P. Processor manufacturer: AMD, Processor socket: Socket AM5, Compatible processor series: AMD Ryzen 9000 Series, AMD Ryzen 8000 Series, AMD Ryzen 7000 Series. Supported memory types: DDR5-SDRAM, Maximum internal memory: 128 GB, Memory slots

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

type: DIMM. Supported storage drive interfaces: SATA III, M.2. Ethernet interface type: Gigabit Ethernet, LAN controller: Realtek RTL8111H. Component for: PC, Motherboard form factor: micro ATX, Motherboard chipset family: AMD | Vendor Homepage: <https://www.asrock.com/MB/AMD/A620AM-P/index.asp#Specification> | Audio chip: Realtek ALC897 | Audio output channels: 7.1 | Component for: PC | Motherboard chipset: AMD A620A | Motherboard chipset family: AMD | Motherboard form factor: micro ATX | Windows operating systems supported: Windows 10 x64/Windows 11 x64 | Compatible processor series: AMD Ryzen 7000 Series/AMD Ryzen 8000 Series/AMD Ryzen 9000 Series | Processor manufacturer: AMD | Processor socket: Socket AM5 | ECC compatibility: Non-ECC | Maximum internal memory: 128 | Memory channels: Dual-channel | Memory slots type: DIMM | Number of memory slots: 2 | Supported memory types: DDR5-SDRAM | Supported storage drive interfaces: SATA III,M.2 | ATX Power connector (24-pin): Yes | CPU fan connector: Yes | EPS power connector (8-pin): Yes | Front panel audio connector: Yes | Number of chassis fan connectors: 3 | Number of CPU fan connectors: 1 | Number of EPS power connectors (8-pin): 1 | Number of SATA III connectors: 2 | RGB LED pin header: Yes | USB 2.0 connectors: 2 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | USB 3.2 Gen 2 (3.1 Gen 2) connectors: 1 | DisplayPort version: 1.4 | DisplayPorts quantity: 1 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | USB 2.0 ports quantity: 4 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Ethernet interface type: Gigabit Ethernet | Ethernet LAN: Yes | LAN controller: Realtek RTL8111H | Wi-Fi: No | Number of M.2 (M) slots: 1 | PCI Express x1 (Gen 3.x) slots: 2 | PCI Express x16 (Gen 4.x) slots: 1 | BIOS memory size: 256 | BIOS type: UEFI AMI | Depth: 229 | Width: 244 | Cables included: SATA | Screws included: Yes | Product Net Weight: 1 | Shipping Box Height: 32 | Unit Calculated Volume: 0.005668 | Unit Calculated Weight: 1.1 | Units per Pallet: 0 | Units per Shipping Box: 10