



Cudy LT500 wireless router Fast Ethernet Dual-band (2.4 GHz 5 GHz) 4G White



Modelis: LT500 OUTDOOR_EU

Gamintojas: CUDY

EAN: 6971690792848

Prekės kodas: 599528

96.99€

VPN support: PPTP/L2TP/OpenVPN/WireGuard/IPSec/Zerotier | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Do not open the appliance housing - risk of electric shock. | WAN connection type: RJ-45 | External power adapter: Yes | Detachable antenna(s): Yes | Dual SIM support: No | SIM card type: NanoSIM | Port triggering: Yes | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | 2G standards: Edge | SIM card slot: Yes | DMZ support: Yes | WLAN data transfer rate (second band): 867 Mbit/s | 2G standards: GSM | Universal Plug and Play (UPnP): Yes | WLAN data transfer rate (first band): 300 Mbit/s | IGMP snooping: Yes | 4G standard: LTE-TDD & LTE-FDD | URL filtering: Yes | 3G standards: WCDMA | Firewall: Yes | Mobile network generation: 4G | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows

Vista Business x64 | MU-MIMO technology: Yes | Windows operating systems supported: Windows

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Vista Business | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows Vista Enterprise | Wall mountable: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | International Protection (IP) code: IP65 | Depth: 100 mm | Wi-Fi standards: Wi-Fi 4 (802.11n) | Antennas quantity: 4 | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Ethernet WAN: Yes | Output voltage: 24 V | Ethernet LAN: Yes | USB port: No | Wi-Fi standards: 802.11b | Supported network protocols: IPv4 / IPv6 | Mac operating systems supported: Yes | Wi-Fi standards: 802.11g | Number of guest networks (2.4 GHz): 1 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Package height: 86 mm | Package depth: 107 mm | Internal memory: 128 MB | Ethernet LAN interface type: Fast Ethernet | Flash memory: 16 MB | Number of guest networks (5 GHz): 1 | Width: 240 mm | Quick installation guide: Yes | Linux operating systems supported: Yes | WLAN data transfer rate (max): 867 Mbit/s | Wi-Fi Multimedia (WMM)/(WME): Yes | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 7 x64 | Product type: Desktop/pole router | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Windows operating systems supported: Windows 10 Education | Windows operating systems supported: Windows XP Professional | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Windows operating systems supported: Windows XP Professional x64 | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 10 Pro x64 | Windows operating systems supported: Windows 8 Enterprise | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 IoT Enterprise | Windows operating systems supported: Windows 7 Professional x64 | Windows operating systems supported: Windows 11 Enterprise | IP address filtering: Yes | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows 11 | Height: 53.7 mm | Windows operating systems supported: Windows 10 Enterprise x64 | Windows operating systems supported: Windows 10 x64 | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows Vista Home Premium x64 | Antenna design: Internal & external | Windows operating systems supported: Windows 10 Education x64 | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | PoE injector included: Yes | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 7 | DHCP client: Yes | Weight: 420 g | Wake-on-LAN ready: Yes | Power source type: PoE | MAC address filtering: Yes | AC input voltage: 100 - 240 V | Ethernet LAN data rates: 10 | Mounting kit: Yes | Ethernet LAN data rates: 100 | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 0 - 100% | Product colour: White | Modulation: 256-QAM | Operating temperature (T-T): -20 - 60 °C | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Security algorithms: WPA2 | Storage relative humidity (H-H): 5 - 95% | Security algorithms: WPA | LED indicators: System, WLAN | Ethernet LAN (RJ-45) ports: 1 | Security algorithms: WPA3 | Filtering: Yes | Package width: 324 mm | Reset button: Yes | Package weight: 785 g