



CyberPower BR700ELCD-FR uninterruptible power supply (UPS) Line- Interactive 0.7 kVA 420 W 8 AC outlet(s)

Modelis: BR700ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856271225

Prekės kodas: 600093

155.99€

Certification: CE | Surge protection features: Fax | Power protection features: Overload | Surge protection features: Network | Surge protection features: Telephone | Output power capacity: 0.7 kVA | UPS topology: Line-Interactive | USB 2.0 ports quantity: 1 | Surge protection features: Modem | Typical backup time at full load: 2 min | Depth: 288 mm | AC outlet types: Type E | LED indicators: Yes | Operating altitude: 0 - 3000 m | USB port: Yes | Operating temperature (T-T): 0 - 40 °C | Battery recharge time: 8 h | Non-operating altitude: 0 - 3000 m | AC outlets quantity: 8 AC outlet(s) | Form factor: Compact | Surge protection features: Digital Subscriber Line (DSL) | Input operation voltage (max): 290 V | Height: 118 mm | Width: 166 mm | Product colour: Black | Storage temperature (T-T):

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

-20 - 50 °C | Surge energy rating: 125 J | Output power: 420 W | Input frequency: 50/60 Hz | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Audible alarm(s): Yes | Cold start: Yes | Cable length: 1.5 m | Ethernet LAN (RJ-45) ports: 2 | Waveform: Sine | Battery technology: Sealed Lead Acid (VRLA) | Response time: 4 ms | Weight: 5.3 kg | Surge protection: Yes | Modem (RJ-11) ports: 2 | Typical backup time at half load: 6 min | Input operation voltage (min): 165 V | Operating relative humidity (H-H): 0 - 90% | Display type: LCD | EMI/RFI noise filtering: Yes | Storage relative humidity (H-H): 0 - 90% | Housing material: Plastic | Compliance certificates: RoHS | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Output frequency: 50/60 Hz | Automatic Voltage Regulation (AVR): Yes