



Switch TP-LINK 8x10Base-T 100Base-TX TL- SF1008P



Modelis: TL-SF1008P

Gamintojas: TP-LINK

EAN: 6935364020682

Prekės kodas: 600197

42.99€

What This Product Does

TL-SF1008P is an 8 10/100Mbps ports unmanaged switch that requires no configuration and provides 4 PoE (Power over Ethernet) ports. It can automatically detect and supply power with all IEEE 802.3af compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Power over Ethernet

4 of the 8 Auto-Negotiation RJ45 ports (port-1 to port-4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs).

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

-Overload Arrangement

TL-SF1008P has the priority function which will help protect the system when the system power is overloaded. If all PoE PDs power consumption is $\geq 57W$, a priority will be arranged among the PoE ports, then the system will cut off the power of the lowest-priority port.

-Port Priority Function

Priority (port-1=port-2=port-3>port-4): This function will help to ensure the normal operation of the system, it means Port 4 will be cut off when all total PoE PDs power consumption exceed 57W. For an example, Port 1, 2 and 4 is using 15.4W (maximum power for per port is 15.4W); the system power is 46.2W in total. If there is an additional PD inserted to Port 3 with 12W, and then the system will cut off the power of Port 4 because of the overloaded power, this means Port 1, 2 will use 15.4W, and Port3 will use 12W, no power will be supplied to Port 4.

Easy To Use

TL-SF1008P is easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the TP-LINK's TL-SF1008P 8-Port 10/100Mbps Desktop Switch with 4-Port PoE is an ideal choice for expanding your home or office network.

- With four PoE ports, transfers data and power on one single cable
- Working with IEEE 802.3af compliant PDs, expands home and office network
- Supports PoE power up to 15.4W for each PoE port
- Supports PoE power up to 57W for all PoE ports
- Requires no configuration and installation

Summary: TP-Link 8-Port 10/100Mbps Desktop PoE Switch with 4-Port. Switch type: Unmanaged.

Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 2000 entries, Switching capacity: 1.6 Gbit/s.

Networking standards: IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x. DC input voltage: 53.5 V.

Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable | Vendor Homepage:

https://www.tp-link.com/au/products/details/cat-42_TL-SF1008P.html#overview | Switch type:

Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports

type: Fast Ethernet (10/100) | Fast Ethernet (copper) ports quantity: 8 | Power connector: DC-in jack |

10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Cable types supported:

Cat3/Cat4/Cat5/Cat5e | Copper ethernet cabling technology: 100BASE-TX/10GBASE-T | Flow control

support: Yes | Full duplex: Yes | Half duplex: Yes | MAC address auto-aging supported: Yes | MAC address auto-learning supported: Yes | Networking standards: IEEE 802.3/IEEE 802.3af/IEEE 802.3u/IEEE 802.3x | Forwarding rate: 1.1904 | MAC address table: 2000 | Store-and-forward: Yes | Switching capacity: 1.6 | IPv4 & IPv6 features: IPv6 portal | Housing material: Metal | LED indicators: Yes | Product colour: Black | Rack mounting: No | Stackable: No | Wall mountable: Yes | Fanless: Yes | AC input frequency: 50 | AC input voltage: 220 | DC input voltage: 53.5 | Input current: 1.31 | Power consumption (max): 66 | Power source: DC/PoE | Power supply included: No | Power over Ethernet (PoE): Yes | Power over Ethernet plus (PoE+) ports quantity: 8 | Total Power over Ethernet (PoE) budget: 57 | Heat dissipation: 248.93 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 98 | Height: 27 | Width: 171 | User guide: Yes | AC adapter included: Yes | Package depth: 280 | Package height: 68 | Package type: Box | Package weight: 980 | Package width: 223 | Sustainability compliance: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Harmonized System (HS) code: 85176990 | Product Net Weight: 0.5 | Shipping Box Height: 7 | Unit Calculated Volume: 0.00441 | Unit Calculated Weight: 0.96 | Units per Shipping Box: 1 | Model: TL-SF1008P | Model name: 8-Port 10/100Mbps Desktop PoE Switch with 4-Port