

Thermaltake Toughpower Gt power supply unit 850 W 24-pin ATX ATX Black

Gamintojas: **THERMALTAKE** · Modelis: **PS-TPT-0850FNFACE-3** · EAN: **4711475647411** · Prekės kodas: **600775**



94,90 €

Kaina su PVM

Be PVM: **78,43 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE/UKCA/ICES/TUV/LVD/RCM/CB/FCC/cTUVus/BSMI/CCC/BIS/S-MARK | PCI Express power connectors (12+4 pin): 1 | PCI Express power connectors (12+4 pin) cable length: 600 mm | Cabling type: Fully-Modular | Combined power (+3.3V): 100 W | Total power: 850 W | Height: 86 mm | On/off switch: Yes | Depth: 140 mm | ATX version: 3.1 | Fan diameter: 12 cm | Purpose: PC/Server | Bearing technology: Hydraulic | Number of fans: 1 fan(s) | Power protection features: Over power | Mean time between failures (MTBF): 100000 h | Power protection features: Short circuit | Power protection features: Over voltage | 80 PLUS certification: 80 PLUS Gold | Power protection features: Under voltage | Power protection features: Over current | PCI Express power connectors (6+2 pin): 4 | Power protection features: Overheating | Power supply unit (PSU) form factor: ATX | Max output current (-12V): 0.3 A | Power Factor Correction (PFC) type: Active | SATA power cable length: 150 | Max output current (+12V): 70.8 A | Hold time: 17 ms | SATA power cable length: 450 mm | Peripheral (Molex) power cable length: 400 mm | Peripheral (Molex) power cable length: 150 mm | Max output current (+5Vsb): 3 A | Motherboard power cable length: 55 cm | Combined power (-12V): 3.6 W | CPU power connector (4+4 pin): Yes | Number of SATA power connectors: 6 | CPU power cable length: 70 cm | Cooling type: Active | Combined power (+12V): 850 W | Package type: Box | Power Good signal delay range: 100 - 250 ms | Motherboard power connector: 24-pin ATX | Operating temperature (T-T): 0 - 40 °C | Combined power (+5V): 100 W | Combined power (+5Vsb): 15 W | Max output current (+3.3V): 20 A | Input current: 10 A | Storage temperature (T-T): -40 - 70 °C | AC input voltage: 100 - 240 V | Peripheral (Molex) power connectors (4-pin): 4 | Max output current (+5V): 20 A | AC input frequency: 50/60 Hz | Product colour: Black | Storage relative humidity (H-H): 5 - 95% | Operating relative humidity (H-H): 5 - 85% | Width: 150 mm

Techninė specifikacija

Specifications

Sandėlio grupė	Power supplies for enclosures [+138][[-85]
----------------	--

Matmenys ir svoris

Matmenys (l × p × A)	28,00cm × 13,00cm × 22,00cm
----------------------	-----------------------------

Svoris	2,58kg
--------	--------