



Thermaltake Toughpower Gt power supply unit 850 W 24- pin ATX ATX Black

Modelis: PS-TPT-0850FNFACE-3

Gamintojas: THERMALTAKE

EAN: 4711475647411

Prekės kodas: 600775

94.99€

Certification: CE/UKCA/ICES/TUV/LVD/RCM/CB/FCC/cTUVus/BSMI/CCC/BIS/S-MARK | Max output current (-12V): 0.3 A | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Overheating | Combined power (+5V): 100 W | Bearing technology: Hydraulic | Max output current (+3.3V): 20 A | 80 PLUS certification: 80 PLUS Gold | Combined power (+5Vsb): 15 W | ATX version: 3.1 | Fan diameter: 12 cm | Power Good signal delay range: 100 - 250 ms | CPU power cable length: 70 cm | Max output current (+5V): 20 A | PCI Express power connectors (6+2 pin): 4 | Combined power (-12V): 3.6 W | Power protection features: Over power | Power protection features: Under voltage | Power protection features: Over current | Number of fans: 1 fan(s) | Motherboard power connector: 24-pin ATX | Combined power (+12V): 850 W | Number of SATA power connectors: 6 | PCI Express power connectors (12+4 pin): 1 | Max output current (+5Vsb): 3 A | Combined power (+3.3V): 100 W | Power Factor Correction (PFC) type: Active |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Peripheral (Molex) power cable length: 400 mm | SATA power cable length: 450 mm | Hold time: 17 ms | CPU power connector (4+4 pin): Yes | SATA power cable length: 150 | Max output current (+12V): 70.8 A | Power supply unit (PSU) form factor: ATX | Purpose: PC/Server | Total power: 850 W | Cabling type: Fully-Modular | Mean time between failures (MTBF): 100000 h | Motherboard power cable length: 55 cm | PCI Express power connectors (12+4 pin) cable length: 600 mm | Peripheral (Molex) power cable length: 150 | Peripheral (Molex) power connectors (4-pin): 4 | Operating relative humidity (H-H): 5 - 85% | On/off switch: Yes | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 40 °C | Package type: Box | Storage temperature (T-T): -40 - 70 °C | Width: 150 mm | Product colour: Black | Cooling type: Active | Depth: 140 mm | AC input voltage: 100 - 240 V | Input current: 10 A | Storage relative humidity (H-H): 5 - 95% | Height: 86 mm