



Thermaltake Toughpower PF1 power supply unit 850 W 24- pin ATX ATX Black



Modelis: PS-TPD-0750FNFAPE-1

Gamintojas: THERMALTAKE

EAN: 4713227525404

Prekės kodas: 600799

128.99€

Certification: CE, UL, TÜV, FCC, CCC, EAC, S-Mark, BSMI | Peripheral (Molex) power cable length: 150 | CPU power cable length: 65 cm | Product colour: Black | Cabling type: Fully-Modular | On/off switch: Yes | Motherboard power connector: 24-pin ATX | Fan location: Top | Peripheral (Molex) power cable length: 500 mm | Number of SATA power connectors: 3 | Hold time: 16 ms | Operating relative humidity (H-H): 20 - 85% | SATA power cable length: 150 | Max output current (-12V): 0.3 A | Total power: 850 W | Mean time between failures (MTBF): 120000 h | PCI Express power connectors (6-pin): 2 | Input current: 10 A | Storage temperature (T-T): -40 - 55 °C | Power supply unit (PSU) form factor: ATX | Silent mode: Yes | Motherboard power cable length: 60 cm | Fan diameter: 12 cm | AC input voltage: 100 - 240 V | Peripheral (Molex) power connectors (4-pin): 4 | Number of fans: 1 fan(s) | Bearing technology: HDB | 80 PLUS certification: 80 PLUS Platinum | AC input frequency: 50 - 60 Hz | Max output current (+5Vsb): 2.5 A | Combined power (+5Vsb): 12.5 W | Noise level: 27.8 dB |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Operating temperature (T-T): 5 - 50 °C | Combined power (-12V): 3.6 W | SATA power cable length: 500 | Max output current (+5V): 20 A | PCI Express power connectors (6+2 pin): 4 | Combined power (+12V): 744 W | Storage relative humidity (H-H): 10 - 95% | Power protection features: Over voltage | Depth: 140 mm | CPU power connector (4+4 pin): Yes | Height: 86 mm | Power protection features: Over current | Peak power: 900 W | Floppy disk drive cable length: 15 cm | Combined power (+3.3V): 100 W | Max output current (+12V): 62 A | Power Factor Correction (PFC) type: Active | Width: 150 mm | Harmonized System (HS) code: 84733020 | Floppy disk drive connector: Yes | Max output current (+3.3V): 20 A | Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA