



Thermaltake TOUGHPOWER GF A3 power supply unit 1050 W 24-pin ATX ATX Black

Modelis: PS-TPD-1050FNFACE-H

Gamintojas: THERMALTAKE

EAN: 4713227537612

Prekės kodas: 600800

129.99€

Certification: CE/FCC/UKCA/ICES/LVD/TUV/cTUVus/CB/CCC/BSMI | Floppy disk drive cable length: 15 cm | EPS power connector (4+4 pin): Yes | Peripheral (Molex) power connectors (4-pin): 4 | PCI Express power connectors (6+2 pin): 5 | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 12 | Power Factor Correction (PFC) type: Active | Max output current (+12V): 87.5 A | Motherboard power connector: 24-pin ATX | Combined power (-12V): 3.6 W | Fan diameter: 12 cm | Combined power (+3.3V): 100 W | Number of fans: 1 fan(s) | AC input voltage: 100 - 240 V | 80 PLUS certification: 80 PLUS Gold | ATX version: 3.0 | Max output current (+5V): 20 A | Purpose: PC | SATA power cable length: 650 | SATA power cable length: 950 mm | AC input frequency: 50/60 Hz | Cabling type: Fully-Modular | Operating relative humidity (H-H): 5 - 85% | Bearing technology: FDB | Total power: 1050 W | Product colour: Black | Combined power (+5Vsb): 15 W | Operating temperature (T-T): 0 - 45 °C | Power supply unit (PSU) form factor: ATX | SATA power cable length:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

800 | Storage temperature (T-T): -40 - 70 °C | Height: 86 mm | Motherboard power cable length: 60 cm | Peripheral (Molex) power cable length: 500 mm | Peripheral (Molex) power cable length: 800 mm | Peripheral (Molex) power cable length: 650 mm | Input current: 16 A | Width: 150 mm | Depth: 140 mm | Storage relative humidity (H-H): 5 - 95% | Mean time between failures (MTBF): 100000 h | Peripheral (Molex) power cable length: 950 mm | Combined power (+12V): 1050 W | Floppy disk drive connector: Yes | PCI Express power connectors (12+4 pin) cable length: 600 mm | SATA power cable length: 500 | Combined power (+5V): 100 W | PCI Express power connectors (12+4 pin): 1 | Max output current (+3.3V): 20 A