



TP-Link Omada 10-Port Gigabit Easy Managed Switch with 8- Port PoE+



Modelis: ES210GMP

Gamintojas: TP-LINK

EAN: 8885020620955

Prekės kodas: 600817

123.99€

Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS
| Compliance certificates: CE | Package type: Box | VLAN support: Yes | DC input voltage: 53.5 V |
Operating temperature (T-T): 0 - 40 °C | Height: 26 mm | Cables included: AC | Switch type: Managed
| Power over Ethernet (PoE): Yes | Transmission distance (max): 0.25 km | Switching capacity: 20
Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 8 | Product colour: Black | Cloud-managed:
Yes | Store-and-forward: Yes | Input current: 2.43 A | Fanless: Yes | Port mirroring: Yes | Power supply
included: Yes | Flow control support: Yes | Total Power over Ethernet (PoE) budget: 123 W | MAC
address table: 8000 entries | Auto-negotiation: Yes | Storage relative humidity (H-H): 5 - 90% |
Networking standards: IEEE 802.3af | Power source: DC | Basic switching RJ-45 Ethernet ports
quantity: 10 | Forwarding rate: 14.88 Mpps | Networking standards: IEEE 802.3at | Auto MDI/MDI-X:
Yes | Packet buffer memory: 4 MB | Virtual LAN features: Port-based VLAN | Networking standards:
IEEE 802.1p | DHCP features: DHCP client | Width: 209 mm | Depth: 126 mm | Wall mountable: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

10G support: No | IGMP snooping: Yes | User guide: Yes | Reset button: Yes | Virtual LAN features: MTU VLAN | Combo SFP ports quantity: 1 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Virtual LAN features: Tagged VLAN | Operating relative humidity (H-H): 10 - 90% | Jumbo frames support: Yes | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Jumbo frames: 15 | Link aggregation: Yes