



ASUS TUF Gaming 850W Platinum power supply unit 20+4 pin ATX ATX Black

Modelis: 90YE0102-B0NA00

Gamintojas: ASUS

EAN: 4711636489911

Prekės kodas: 600879

190.99€

Mean time between failures (MTBF): 120000 h | 80 PLUS certification: 80 PLUS Platinum | Warranty period: 8 year(s) | Package width: 304 mm | Cooling type: Active | PCI Express power connectors (16-pin): 1 | Product colour: Black | Power supply unit (PSU) form factor: ATX | Depth: 150 mm | Package depth: 188 mm | Width: 150 mm | Height: 86 mm | Number of fans: 1 fan(s) | Weight: 1.48 kg | AC input voltage: 100 - 240 V | ATX version: 3.1 | Fan diameter: 13.5 cm | Total power: 850 W | Combined power (+3.3V): 125 W | Package weight: 3.29 kg | Compliance certificates: RoHS | Power protection features: Under voltage | Power protection features: Over current | Peripheral (Molex) power connectors (4-pin): 3 | PCI Express power connectors (6+2 pin): 3 | Power protection features: Overheating | Bearing technology: Ball bearing | On/off switch: Yes | Cabling type: Fully-Modular | Package height: 127 mm | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Over power | Package type: Box | Cables included: AC, CPU,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

PCIe, Peripheral (Molex), SATA | Purpose: PC | Motherboard power connector: 20+4 pin ATX | Max output current (+5Vsb): 3 A | Max output current (-12V): 0.3 A | Number of SATA power connectors: 6 | CPU power connector (4+4 pin): Yes | Combined power (+5V): 125 W | Max output current (+3.3V): 25 A | Motherboard power cable length: 61 cm | Max output current (+12V): 70.83 A | Combined power (+12V): 850 W | Combined power (-12V): 3.6 W | Power Factor Correction (PFC) type: Active | Combined power (+5Vsb): 15 W | Max output current (+5V): 25 A