



TP-Link Tapo TC90 KIT security camera Bulb IP security camera Outdoor 2304 x 1296 pixels Ceiling/Wall/Pole

Modelis: TC90 KIT

Gamintojas: TP-LINK

EAN: 1210002605328

Prekės kodas: 600885

91.98€

Certification: CB, CE, FCC, DOE, CEC, RCM, KC, JFR,VCCI,NCC, BSMI, NTRA, IP65 | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11a | Audio output channels: 2.0 channels | Tilt angle range: 0 - 90° | AC input frequency: 50-60 Hz | AC input voltage: 100-240 V | Product colour: White | Connectivity technology: Wireless | Number of microphones: 1 | Mounting type: Ceiling/Wall/Pole | Maximum memory card size: 512 GB | Number of sensors: 1 | Number of lenses: 1 | Pan range: 0 - 340° | Zoom capability: Yes | Total megapixels: 3 MP | Optical sensor size: 25.4 / 2.8 mm (1 / 2.8") | Maximum aperture number: 1.6 | Mobile operating systems supported: Android 7.0 | Night vision:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Yes | Placement supported: Outdoor | Mobile operating systems supported: iOS 12 | Audio input channels: 2.0 channels | Frame rate: 15 fps | Built-in HDD: No | Infra-red wavelength: 850 nm | Fixed focal length: 4 mm | Video motion detection: Yes | Alert notification type: Snapshot alert message | Noise reduction: Yes | Live view: Yes | Number of illumination LEDs: 4 | Built-in speaker(s): Yes | LED type: IR/White | Sensor type: CMOS | Image quality adjustment: DNR | Camera tilt control: Yes | Motion sensor: Yes | Progressive scan: Yes | Cloud-managed: Yes | Weatherproof: Yes | Camera pan control: Yes | Package weight: 1.32 kg | Security algorithms: SSL/TLS | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN: No | Depth: 116.1 mm | Siren noise level: 97.2 dB | Storage temperature (T-T): -20 - 60 °C | Maximum resolution: 2304 x 1296 pixels | Wide Dynamic Range (WDR): Yes | Lens viewing angle, diagonal: 100.6° | Reset button: Yes | Supported graphics resolutions: 2304 x 1296 | Form factor: Bulb | Package depth: 200 mm | Battery technology: Lithium-Ion (Li-Ion) | Width: 130.9 mm | Lens viewing angle, horizontal: 84.4° | Package height: 148 mm | Wi-Fi: Yes | Compatible memory cards: MicroSD (TransFlash) | Number of batteries supported: 1 | Storage relative humidity (H-H): 0 - 90% | Lens viewing angle, vertical: 44.3° | Power source type: Battery, Solar | Built-in siren: Yes | Wi-Fi standards: 802.11b | Microphone in: Yes | Security algorithms: WPA2-PSK | Wi-Fi standards: 802.11a | Type: IP security camera | Built-in microphone: Yes | Wi-Fi standards: 802.11g | Built-in light: Yes | Night vision distance: 10 m | Audio system: 2-way | International Protection (IP) code: IP65 | Security algorithms: WPA | Number of cameras: 1 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Package width: 247 mm | Height: 84.1 mm | Operating temperature (T-T): -20 - 45 °C