



## DeepCool PN850M power supply unit 850 W 20+4 pin ATX ATX Black

Modelis: R-PN850M-FC0B-EU

Gamintojas: DEEPCOOL

EAN: 6933412741053

Prekės kodas: 601268

# 96.99€

Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: RoHS |  
Compliance certificates: CE | Compliance certificates: EAC | Compliance certificates: Federal  
Communications Commission (FCC) | Compliance certificates: CCC | Peripheral (Molex) power  
connectors (4-pin): 2 | Product colour: Black | Package type: Box | Depth: 140 mm | Operating  
temperature (T-T): 0 - 40 °C | Cables included: AC | Cooling type: Active | AC input frequency: 50/60  
Hz | On/off switch: Yes | AC input voltage: 100 - 240 V | Input current: 10 - 5 A | Width: 150 mm | 80  
PLUS certification: 80 PLUS Gold | Height: 86 mm | Power protection features: Over power | Hold  
time: 16 ms | Power protection features: Surge & inrush protection (SIP) | Power protection features:  
Overheating | Power protection features: Surge protection | Peripheral (Molex) power cable length:  
850 mm | Power protection features: Short circuit | Power protection features: Over voltage |  
Combined power (-12V): 3.6 W | Power protection features: No load operation | Max output current (-  
12V): 0.3 A | Combined power (+3.3V): 110 W | Power supply unit (PSU) form factor: ATX | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

protection features: Under voltage | Max output current (+12V): 70.5 A | Motherboard power cable length: 55 cm | Power Factor Correction (PFC) type: Active | SATA power cable length: 450 mm | Bearing technology: FDB | Purpose: PC | SATA power cable length: 650 | CPU power cable length: 70 cm | Power Good signal delay range: 100 - 150 ms | Max output current (+3.3V): 20 A | ATX version: 3.1 | Combined power (+5V): 110 W | Motherboard power connector: 20+4 pin ATX | Fan diameter: 12 cm | Number of SATA power connectors: 8 | Number of fans: 1 fan(s) | Total power: 850 W | Max output current (+5Vsb): 3 A | Combined power (+5Vsb): 15 W | SATA power cable length: 750 mm | SATA power cable length: 550 | Max output current (+5V): 20 A | Efficiency: 90% | Mean time between failures (MTBF): 100000 h | Fan location: Top | CPU power connector (4+4 pin): Yes | Cable tie(s) included: Yes | Cabling type: Fully-Modular | ATX power connector (20+4 pin): Yes | PCI Express power connectors (6+2 pin): 3 | Combined power (+12V): 846 W | Sustainability certificates: Triman | Sustainability certificates: ErP | Sustainability compliance: Yes | PCI Express power connectors (16-pin): 1