

iiyama ProLite XCB4994DQSU-B1 computer monitor 124.5 cm (49") 5120 x 1440 pixels Dual QHD LCD Black

Gamintojas: IIYAMA · Modelis: XCB4994DQSU-B1 · EAN: 4948570127993 · Prekės kodas: 601599



693,90 €

Kaina su PVM

Be PVM: 573,47 €

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 124.5 cm (49") Black
- ✓ Height adjustment 13 cm Built-in speaker(s)
- ✓ HDMI HDMI version: 2.0 DisplayPorts quantity: 2 DisplayPort version: 1.2
- ✓ Screen shape: Curved
- ✓ Maximum refresh rate: 120 Hz Response time: 2 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 5120 x 1440 pixels Dual QHD Panel type: VA
- ✓ Energy efficiency class (SDR): G ErP CE, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE



Aprašymas

The ProLite XCB4994DQSU-B1 gives professionals the screen space they need to work more efficiently. Its expansive 49-inch display, 32:9 aspect ratio and 5120 x 1440 Dual QHD resolution provide the workspace of two QHD monitors in one seamless screen. Users can keep multiple applications, documents, dashboards or timelines open side by side without switching between windows or working around central bezels. The 1000R curved VA panel brings the entire workspace into a more natural field of view, making it easier to monitor information across the screen while reducing unnecessary head and eye movement. High contrast, vivid colours, wide viewing angles and 400 cd/m2 brightness keep text, graphics and detailed content clear in bright office environments. A 2ms GTG response time and Adaptive Sync support smooth scrolling, video playback and work with moving content. Flicker-free technology and a blue light reducer help maintain visual comfort during long working sessions. Height and tilt adjustments allow users to create a more comfortable workstation, while the three-side borderless design gives professional setups a clean, modern

appearance. Dual HDMI and DisplayPort inputs provide flexible connectivity for multiple devices, and integrated 2 x 5W speakers support video calls, presentations and everyday media without additional desktop equipment. By replacing a dual-monitor setup with one uninterrupted 49-inch workspace, users gain more room to organise their work, compare information and stay focused throughout the day.

Techninė specifikacija

Specifications	
Sandėlio grupė	Monitore [+1547][-114]
Display	
Display diagonal	124.5 cm (49")
Display resolution	5120 x 1440 pixels
Native aspect ratio	32:9
Display technology	LCD
Touchscreen	No
HD type	Dual QHD
Panel type	VA
Response time	2 ms
Screen shape	Curved
Contrast ratio (typical)	3000:1
Maximum refresh rate	120 Hz
Display number of colours	16.7 million colours
Display brightness (typical)	400 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Screen curvature rating	1000R
Contrast ratio (dynamic)	80000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.233 x 0.233 mm
Horizontal scan range	30 - 185 kHz
Viewable size, horizontal	119.2 cm
Viewable size, vertical	33.5 cm
Display diagonal (metric)	124 cm
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
sRGB coverage (typical)	100%
NTSC coverage (typical)	80%

Performance

NVIDIA G-SYNC	Yes
AMD FreeSync	Yes
VESA Adaptive Sync support	Yes
Flicker-free technology	Yes
Low Blue Light technology	Yes

Multimedia

Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	10 W

Design

Market positioning	Professional
Product colour	Black

Ports & interfaces

Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of downstream ports	4
USB Type-A downstream ports quantity	2
USB Type-C downstream ports quantity	2
HDMI ports quantity	2
HDMI version	2
DisplayPorts quantity	2
DisplayPort version	1.2
HDCP	Yes

Ergonomics

VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Adjustable height (max)	13 cm

Tilt adjustment	Yes
Tilt angle range	-5 - 21°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Russian, Ukrainian
Power	
Energy efficiency class (SDR)	G
Power consumption (typical)	44 W
Power consumption (standby)	44 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Weight & dimensions	
Width (with stand)	1150.5 mm
Depth (with stand)	356 mm
Height (with stand)	541 mm
Weight (with stand)	11.9 kg
Height (without stand)	411 mm
Weight (without stand)	9.7 kg
Packaging data	
Package width	1920 mm
Package depth	370 mm
Package height	485 mm
Package weight	22.3 kg
Package type	Box
USB cable length	1.8 m
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Power cable length	1.8 m
Sustainability	
Sustainability certificates	ErP

Other features

Packaging content	quick start guide, safety guide
Weight	11.9 kg
Width	1150.5 mm
Depth	356 mm
Compliance certificates	CE, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
User controls	picture adjust (contrast, brightness, ECO, ACR, OD, Adaptive Sync, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp., user preset), PiP/PbP (PiP/PbP, sub source, PiP position, PiP size, swap, audio input), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB charge, USB update), input select, audio settings (volume, mute), recall (recall all?)
Control panel	Navigation (power) button: Center (Main Menu/Execution), Front (Move Down/N/A), Back (Move Up/Input Select), Right (Move Right/Volume), Left (Move Left/Submenu)

Matmenys ir svoris

Matmenys (I × P × A)	130,00cm × 51,00cm × 35,00cm
----------------------	------------------------------