



# TP-Link Omada 24-Port Gigabit and 4-Port 10GE SFP+ L2+ Managed Switch with 24-Port PoE+



Modelis: SG3428XMP

Gamintojas: TP-LINK

EAN: 1210002611619

Prekės kodas: 602661

## 498.99€

Operating temperature (T-T): 0 - 45 °C | Height: 44 mm | Operating relative humidity (H-H): 10 - 90%  
| Rack mounting: Yes | AC input frequency: 50/60 Hz | Ethernet LAN data rates: 10,100,1000 Mbit/s |  
Power source: AC | Quick start guide: Yes | Power consumption (max): 486.2 W | Cables included:  
LAN (RJ-45) | Power over Ethernet (PoE): Yes | LED indicators: Yes | Width: 440 mm | Form factor: 1U  
| Networking standards: IEEE 802.1w | AC input voltage: 100 - 240 V | Number of fans: 2 fan(s) |  
Web-based management: Yes | Storage relative humidity (H-H): 5 - 90% | Depth: 330 mm | Total  
Power over Ethernet (PoE) budget: 384 W | Product colour: Black | Networking standards: IEEE  
802.11d | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking  
standards: IEEE 802.1s | Virtual LAN features: Private VLAN | Spanning tree protocol: Yes | Jumbo

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

frames: 9000 | Head-of-line (HOL) blocking: Yes | Number of VLANs: 4000 | Gigabit Ethernet (copper) ports quantity: 24 | Link aggregation: Yes | Jumbo frames support: Yes | SSH/SSL support: Yes | MIB support: Yes | 10G support: Yes | Console port: RJ-45/micro-USB | Cloud-managed: Yes | Virtual LAN features: Port-based VLAN | Rate limiting: Yes | IP-MAC-Port binding: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Broadcast storm control: Yes | VLAN support: Yes | Number of static routes: 48 | Forwarding rate: 95.23 Mpps | Loop protection: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switching capacity: 128 Gbit/s | Flow control support: Yes | MAC address table: 16000 entries | IGMP snooping: Yes | Virtual LAN features: MAC address-based VLAN | Heat dissipation: 1658.78 BTU/h | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 24 | Virtual LAN features: Tagged VLAN | Packet buffer memory: 12 MB | Power supply included: Yes | Policy-based routing: Yes | Multicast support: Yes | Virtual LAN features: Protocol-based VLAN | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | System event log: Yes | Virtual LAN features: Voice VLAN | Management protocols: SNMPv1/v2c/v3, SNTP | DHCP features: DHCPv6 client | Port mirroring: Yes | BPDU filtering/protection: Yes | DHCP features: DHCP snooping | Switch layer: L2+ | Switch type: Managed | Active link detection: Yes | DHCP features: DHCPv6 snooping | DHCP features: DHCP server | DHCP features: DHCP client | DHCP features: DHCP relay