



TP-Link JetStream 18- Port Gigabit Smart Switch with 16-Port PoE+



Modelis: TL-SG2218P

Gamintojas: TP-LINK

EAN: 4897098689509

Prekės kodas: 602665

266.99€

Certification: CE, FCC, RoHS | Multicast features: Multicast forwarding | Configuring Location Settings (CLI): Yes | Switching capacity: 26.78 Gbit/s | Power source: DC/PoE | VLAN support: Yes | Rate limiting: Yes | Form factor: 1U | Basic switching RJ-45 Ethernet ports quantity: 16 | DHCP features: DHCP client | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Web-based management: Yes | MAC address filtering: Yes | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Forwarding rate: 26.78 Mpps | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3az | Operating temperature (T-T): 0 - 50 °C | Height: 44 mm | Cables included: LAN (RJ-45) | Power supply included: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power over Ethernet (PoE): Yes | ARP inspection: Yes | Width: 440 mm | Rack mounting: Yes | Package type: Box | Broadcast storm control: Yes | Jumbo

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

frames: 9 | Static port security: Yes | Total Power over Ethernet (PoE) budget: 150 W | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1x | Storage relative humidity (H-H): 5 - 90% | Ethernet LAN data rates: 10,100,1000 Mbit/s | Networking standards: IEEE 802.3u | IP routing: Yes | Spanning tree protocol: Yes | DHCP features: DHCP snooping | BPDU filtering/protection: Yes | Policy-based routing: Yes | AC input voltage: 100 - 240 V | Loop protection: Yes | Access Control List (ACL): Yes | Jumbo frames support: Yes | Depth: 180 mm | Link aggregation: Yes | Switch layer: L2/L2+ | System event log: Yes | DHCP features: DHCP relay | MAC address table: 8000 entries | Auto-negotiation: Yes | LED indicators: Yes | Cloud-managed: Yes | Auto MDI/MDI-X: Yes | 10G support: No | User guide: Yes | SSH/SSL support: Yes | Multicast support: Yes | Authentication: MAC-based authentication, Port-based authentication | Product colour: Black | Flow control support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes