



Power Supply BE QUIET ATX PC 200 - 240 V 450 W BP009EU



Modelis: BP009EU

Gamintojas: BE QUIET

EAN: 4260052191859

Prekės kodas: 602765

60.98€

Proven Reliability, Quiet Operation

System Power 11 450W has been built with value-oriented users in mind that do not want to pass on reliability and quietness. Elaborate features such as ATX 3.1 compatibility and a temperature-controlled fan and a remarkably low stand-by-drain underline the value System Power 11 450W offers even at entry-level.

- ATX 3.1 PSU with support for PCIe 5.1 GPUs and GPUs with 6+2 pin connectors
- Temperature-controlled 120mm quality fan reduces system noise
- Rock-solid stability with a strong 12V-rail
- Tight voltage regulation using DC-to-DC technology
- 2 PCIe 6-2 connectors
- Dependable operation to support powerful GPUs
- Stand-by drain of less than 0.15 watts

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- 80 PLUS® Bronze efficiency (up to 89.0%)
- Attractive black flat cables
- Complete suite of top safety features
- Product conception, design and quality control in Germany

Summary: be quiet! System Power 11 450W. Total power: 450 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: CB, CE, RoHS, TÜV mark, UKCA, WEEE | Vendor Homepage: <https://www.bequiet.com/en/download/products> | AC input frequency: 50 | AC input voltage: 200 - 240 | Combined power (+12V): 450 | Combined power (+3.3V): 110 | Combined power (+5V): 110 | Combined power (+5Vsb): 15 | Combined power (-12V): 3.6 | Efficiency: 89 | Hold time: 16.86 | Input current: 4 | Max output current (+12V1): 37.5 | Max output current (+3.3V): 20 | Max output current (+5V): 20 | Max output current (+5Vsb): 3 | Max output current (-12V): 0.3 | Number of +12V rail(s): 1 | Power factor: 0.98 | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Surge & inrush/Under voltage | Total power: 450 | Cabling type: Non-Modular | CPU power connector (4+4 pin): Yes | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 5 | PCI Express power connectors (6+2 pin): 2 | Peripheral (Molex) power connectors (4-pin): 1 | 80 PLUS certification: 80 PLUS Bronze | ATX version: 3.1 | Bearing technology: Rifle | EPS version: 2.92 | Mean time between failures (MTBF): 100000 | Noise level: 19.1 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Fan speed: 0 - 1800 | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Compliance certificates: CB/CE/RoHS/TÜV mark/UKCA/WEEE | Waste Electrical and Electronic Equipment (WEEE) compliance: Yes | Depth: 86 | Height: 140 | Weight: 1700 | Width: 150 | Package depth: 268 | Package height: 97 | Package type: Box | Package weight: 2100 | Package width: 195 | Sustainability certificates: ENERGY STAR/ErP | Products per shipping (inner) case: 6 | Shipping (inner) case gross weight: 13600 | Shipping (inner) case height: 218 | Shipping (inner) case length: 556 | Shipping (inner) case width: 311 | Cable ties included: Yes | Screws included: Yes | Product Net Weight: 1.7 | Shipping Box Height: 21.8999996185303 | Unit Calculated Volume: 0.006732 | Unit Calculated Weight: 2.3 | Units per Pallet: 0 | Units per Shipping Box: 6