

iiyama ProLite TW1025LASC-B3PNR kompiuterio monitorius 25,6 cm (10.1") 1280 x 800 pikseliai WXGA LED Lietimui jautrus ekranas Daugybė naudotojų Juoda

 Gamintojas: **IIYAMA** · Modelis: **TW1025LASC-B3PNR** · EAN: **4948570127146** · Prekės kodas: **603503**


338,90 €

Kaina su PVM

 Be PVM: **280,08 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 25,6 cm (10.1") Juoda
- ✓ Įmontuoti garsiakalbiai Integruota kamera
- ✓ Ekranas forma: Plokščias
- ✓ Reakcijos laikas: 25 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1280 x 800 pikseliai WXGA Skydo tipas: IPS
- ✓ ErP CE, EAC, REACH, RoHS, UKCA, WEEE





Aprašymas

The ProLite TW1025LASC-B3PNR touch panel PC is a perfect choice for high-use environments such as booking rooms, information desks or other corporate and hospitality applications. The Optical Bonded Projective Capacitive (PCAP) 10-point touch technology ensures a seamless and accurate touch response and a lower light reflection, in addition, the display is protected against humidity and potential moisture development. Thanks to the pre-installed Android 16 operating system, it is possible to easily customize the monitor by installing applications directly to it. The Power over Ethernet technology (POE) allows to provide both data connection and power by a single cable, simplifying all installations. Thanks to the NFC/RFID reader, the touch panel PC allows to communicate wirelessly with enabled devices or tags within close proximity and the RGB Led bar will clearly and intuitively indicate the availability status of the room. Additionally, it integrates effortlessly with iiSignage2 , iiyama's Content Management System (CMS), giving you full control over your messages and advertising, in landscape portrait and face-up position. Together with the built-in 5 megapixel camera, microphone and speakers it offers limitless, interactive installation possibilities.

Techninė specifikacija

Display	
Display diagonal	25.6 cm (10.1")
Display resolution	1280 x 800 pixels
Native aspect ratio	16:10
Display technology	LED
Touchscreen	Yes
HD type	WXGA
Panel type	IPS
Response time	25 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.7 million colours
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Number of simultaneous touchpoints	10
Display brightness (typical)	450 cd/m²
Display brightness	390 cd/m²
Response time measurement type	GTG (Gray to Gray)
Viewing angle, horizontal	160°
Viewing angle, vertical	160°

Pixel pitch	0.1692 x 0.1692 mm
Viewable size, horizontal	21.7 cm
Viewable size, vertical	13.5 cm
Display diagonal (metric)	25.5 cm
Surface hardness	6H
Colour depth	8 bit
Performance	
Operating hours (hours/days)	24/7
Operating system version	13
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	Yes
Number of speakers	2
RMS rated power	4 W
Megapixel (approx.)	5 MP
Design	
Product colour	Black
Front bezel colour	Black
Glass thickness	1.85 mm
Ports & interfaces	
Built-in USB hub	Yes
HDMI	No
USB Touch port	Yes
Card reader integrated	Yes
Compatible memory cards	SD
Network	
Wi-Fi	Yes
Wi-Fi standards	Wi-Fi 5 (802.11ac), Wi-Fi 4 (802.11n), 802.11g, 802.11b
Bluetooth	Yes
Bluetooth version	5.2
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	75 x 75 mm

Cable management	Yes
Power	
Power consumption (typical)	10 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC adapter output voltage	12 V
Power supply type	External
Weight & dimensions	
Width (with stand)	259.5 mm
Depth (with stand)	28 mm
Height (with stand)	178.5 mm
Weight (with stand)	1.1 kg
Weight (without stand)	1.6 kg
Packaging data	
Package width	363 mm
Package depth	65 mm
Package height	225 mm
Packaging content	
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
AC adapter included	Yes
Google applications	Google Chrome, Gmail, Google Calendar
Brightness	390 cd/m ²
Packaging content	AC adapter, interchangeable plugs (EU/UK), cable cover/wall mount
Built-in processor	Yes
Active display area (W x H)	216.6 x 135.4 mm
USB ports quantity	3
Weight	1.1 kg
Height	178.5 mm
Width	259.5 mm
Depth	28 mm
Compliance certificates	CE, EAC, REACH, RoHS, UKCA, WEEE

Ethernet LAN (RJ-45) ports	1
User controls	Power switch
Touch method	finger, glove (latex), capacitive stylus
Control panel	Power switch
Matmenys ir svoris	
Matmenys (I × P × A)	36,00cm × 23,00cm × 7,00cm
Svoris	1,61kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas 1](#) objects.icecat.biz/objects/139431265_73722037.mp4
- › [Vaizdo įrašas 2](#) objects.icecat.biz/objects/139431265_73722039.mp4
- › [Vaizdo įrašas 3](#) objects.icecat.biz/objects/139431265_73722041.mp4
- › [Vaizdo įrašas 4](#) objects.icecat.biz/objects/139431265_73722042.mp4
- › [Vaizdo įrašas 5](#) objects.icecat.biz/objects/139431265_73722044.mp4
- › [Vaizdo įrašas 6](#) objects.icecat.biz/objects/139431265_73722046.mp4

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL
iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt